Product data sheet

Specifications





Residual current circuit breaker (RCCB), Multi9 ID, 4P, 63A, A-SI type, 30mA

M9R31463

(Discontinued on: May 19, 2023

(!) End-of-service on: Jun 30, 2023

Main

Range	Multi9
Product Name	Multi9 ID
Product Or Component Type	Residual current circuit breaker (RCCB)
Device Short Name	ID
Device Application	Distribution
Poles Description	4P
Neutral Position	Left
Line Rated Current	63 A
Network Type	AC
Earth-Leakage Sensitivity	30 mA
Earth-Leakage Protection Time Delay	Instantaneous
Earth-Leakage Protection Class	Type A-SI (Super Immunised)

Complementary

Complementary	
Network Frequency	50 Hz
[Ue] Rated Operational Voltage	380415 V AC 50 Hz
Residual Current Tripping Technology	Voltage independent
Rated Breaking And Making Capacity	Idm 630 A EN/IEC 61008-1
Rated Conditional Short-Circuit Current	Inc 10 kA
[Ui] Rated Insulation Voltage	440 V AC 50 Hz EN/IEC 61008-1
[Uimp] Rated Impulse Withstand Voltage	6 kVEN/IEC 61008-1
Surge Current	3000 A
Contact Position Indicator	Yes
Control Type	Toggle
Local Signalling	ON, OFF, fault trip
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 Mm Pitches	8
Height	3.19 in (81 mm)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Width	2.83 in (72 mm)
Depth	2.87 in (73 mm)
Net Weight	0.99 lb(US) (0.45 kg)
Color	Gray
Mechanical Durability	20000 cycles
Electrical Durability	2000 cycles
Locking Options Description	Padlocking device
Connections - Terminals	Tunnel type terminal top or bottom) 0.000.05 in ² (135 mm ²) - rigid Tunnel type terminal top or bottom) 0.000.04 in ² (125 mm ²) - flexible Tunnel type terminal top or bottom) 3 0.02 in ² (16 mm ²) - rigid Tunnel type terminal top or bottom) 3 0.02 in ² (10 mm ²) - flexible Tunnel type terminal top or bottom) 0.000.04 in ² (125 mm ²) - flexible with ferrule
Wire Stripping Length	0.59 in (15 mm) for top or bottom connection
Tightening Torque	30.98 lbf.in (3.5 N.m) top or bottom

Environment

Standards	EN/IEC 61008-1
Product Certifications	CE
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution Degree	3
Electromagnetic Compatibility	8/20 μs impulse withstand, 3000 A EN/IEC 61008-1
Tropicalisation	2 IEC 60068-1
Relative Humidity	95 % 131 °F (55 °C)
Ambient Air Temperature For Operation	-13104 °F (-2540 °C)
Ambient Air Temperature For Storage	-40140 °F (-4060 °C)

Ordering and shipping details

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.03 in (7.7 cm)
Package 1 Width	3.31 in (8.4 cm)
Package 1 Length	3.62 in (9.2 cm)
Package 1 Weight	13.47 oz (382.0 g)
Unit Type Of Package 2	S03
Number Of Units In Package 2	27
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	23.81 lb(US) (10.801 kg)

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations