Product data sheet

Specifications





Power quality meter, PowerLogic ION7400, Standard, integrated display, 512 MB, 256 s/c

METSEION7410

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 8,928.36 USD

Main

| Range | PowerLogic |
|---------------------------|--------------------|
| Product Name | PowerLogic ION7400 |
| Device Short Name | ION7410 |
| Product Or Component Type | Power meter |

| Compl | ementary |
|-------|----------|
| | |

| Complementary | |
|------------------------|---|
| Power Quality Analysis | EN 50160 2010 compliance report IEEE 519 2014 compliance report IEC 61000-4-30 class S power quality measurement up to the 63rd harmonic harmonic distortion waveform capture voltage sag and swell detection programmability (logic and math functions) IEC 62586 power quality monitoring IEC 61000-4-15 disturbance direction detection rapid voltage change |
| Device Application | Data aggregation Revenue billing WAGES metering Power monitoring |
| Type Of Measurement | Current Voltage Frequency Active and reactive power total Apparent power total Power factor total Active and reactive power per phase, rms Apparent power per phase, rms Power factor per phase, rms Active and reactive energy Apparent energy |
| Supply Voltage | 2060 V DC +/- 10 % |
| Network Frequency | 50 Hz 60 Hz |
| Line Rated Current | 10 A 1 A 5 A |
| Poles Description | 1P + N 3P + N 3P |
| Power Consumption In W | 17 W |
| Display Type | Colour TFT LCD |
| Display Resolution | 320 x 240 pixels QVGA |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Sampling Rate | 256 samples/cycle |
|-----------------------------|---|
| Measurement Current | 5010000 mA |
| Analogue Input Type | Voltage (impedance 5 MOhm) Current (impedance 0.3 mOhm) |
| Measurement Voltage | 57400 V AC 4269 Hz between phase and neutral 100690 V AC 4269 Hz between phases |
| Frequency Measurement Range | 4269 Hz |
| Number Of Inputs | 3 digital 30 V AC 3 digital 60 V DC |
| Measurement Accuracy | Current +/- 0.1 % Voltage +/- 0.1 % Active energy +/- 0.2 % |
| Accuracy Class | Class 0.2S active energy IEC 62053-22 Class 0.2 active energy ANSI C12.20 Class 0.2 active power IEC 61557-12 Class 0.5S reactive energy IEC 62053-24 Class 0.5 power factor IEC 61557-12 Class 0.2 voltage IEC 61557-12 Class 0.2 current IEC 61557-12 Class 0.2 frequency IEC 61557-12 Class 0.2 active energy IEC 61557-12 |
| Number Of Outputs | 1 pulse |
| Information Displayed | Voltage Current Frequency Power Energy consumption Harmonic distortion |
| Communication Port Protocol | Modbus RTU 115 kbauds - 2-wire ION 115 kbauds - 2-wire DNP3 IEC 61850 Modbus TCP/IP Ethernet Modbus TCP/IP daisy chain 10/100 Mbit/s RSTP 801.1d 2004 Ansi C12.19 DLMS |
| Communication Port Support | ETHERNET Screw terminal block RS485 Optical probe fiber optic Mini B USB USB |
| Communication Network Type | IPv6 (internet protocol) |
| Data Recording | Data logs Sag and swell logs Waveform logs Trending/forecasting Sequence of event recording GPS synchronisation Harmonics logs Time stamping Alarm logs Event logs Event logs Min/max of instantaneous values 50 data recorders |
| Memory Capacity | 512 MB |
| Web Services | Customizable home page File upload/download via FTP File upload/download via SFTP Web server Alarm notification by e-mail Viewing of captured waveform (FTP) Viewing of captured waveform (web) HTTPS server |

| Communication Service | SNMP |
|------------------------|--|
| | SMTP e-mail notification |
| | RSTP support |
| | DHCP |
| | NTP time synchronization |
| | PTP time synchronization |
| | |
| Cybersecurity | Enable/disable communication ports |
| | Port hardening |
| | Syslog protocol support |
| | Password protection |
| | Robust security logs |
| Mounting Mode | Flush-mounted |
| Mounting Support | Framework |
| Type Of Installation | Indoor installation |
| Installation Category | 111 |
| Safety Construction | III400690 V conforming to IEC 61010-1:ed. 3 |
| - | III400690 V conforming to EN 61010-1:ed. 3 |
| | III347600 V conforming to UL 61010-1:ed. 3 |
| | III347600 V conforming to CSA C22.2 No 61010-1:ed. 3 |
| Standards | IEC 61557-12 |
| | IEC 61326-1 |
| | IEC 62052-11 |
| | IEC 62053-24 |
| | IEC 62053-22 |
| | IEEE 1588 |
| | IEC 62586 |
| | |
| Product Certifications | CE |
| | CULus |
| | N998 |
| Width | 3.86 in (98 mm) |
| Depth | 3.09 in (78.5 mm) |
| Height | 4.41 in (112 mm) |
| Net Weight | 24.90 oz (706 g) |

Environment

| Electromagnetic Compatibility | Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Immunity to impulse waves conforming to IEC 61000-4-12 Conducted and radiated emissions conforming to EN 55022 Conducted and radiated emissions conforming to FCC part 15 Conducted and radiated emissions conforming to ICES-003 Conducted RF disturbances (2150 Hz) conforming to CLC/TR 50579 Surge withstand conforming to IEEE C37.90.1 |
|--|--|
| Ip Degree Of Protection | IP54 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529 |
| Relative Humidity | 595 % |
| Ambient Air Temperature For Operation | -13158 °F (-2570 °C) |
| Ambient Air Temperature For Storage | -40185 °F (-4085 °C) |
| Operating Altitude | 9842.52 ft (3000 m) |

Ordering and shipping details

| Category | US10PM109753 |
|-------------------|---------------|
| Discount Schedule | 0PM1 |
| Gtin | 3606481384577 |
| Returnability | No |
| Country Of Origin | US |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 5.51 in (14.0 cm) |
| Package 1 Width | 5.51 in (14.0 cm) |
| Package 1 Length | 7.28 in (18.5 cm) |
| Package 1 Weight | 2.27 lb(US) (1.03 kg) |

4

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Rohs Exemption Information

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|--|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |