Product data sheet

Specifications

Vertical uprights height 1000mm. zinc-coated steel. Supply: 2 standard uprights.

NSYTVR10

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 92.14 USD

Main

Range	Thalassa
Accessory / Separate Part Category	Mounting accessory
Product Or Component Type	Technical upright
Enclosure Nominal Dimensions	- H: 39.37 in (1000 mm)
Range Compatibility	Spacial Spacial SF Spacial Spacial SM

Complementary

Height	Nominal 39.37 in (1000 mm) Real 34.45 in (875 mm)

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
Gtin	3606480185052
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.57 in (4.0 cm)
Package 1 Width	2.36 in (6.0 cm)
Package 1 Length	34.45 in (87.5 cm)
Package 1 Weight	6.61 lb(US) (3.0 kg)

Contractual warranty

Warranty	18 months

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Sustainability

Green Premium^TM label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency   RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation   REACh Declaration

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

EU RoHS Declaration

China Rohs Regulation   China RoHS declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure   Product Environmental Profile

Circularity Profile   No need of specific recycling operations