Product data sheet

Specifications







Mini circuit breaker, QO, 100A, 2 pole, 120/240VAC, 10kA, plug in, AC shunt

QO21001021

Product availability: Stock - Normally stocked in distribution facility

Price*: 378.00 USD

Main

Product	Miniature circuit-breaker	
Range	QO	
Current Rating	100 A	
Voltage Rating	120/240 V AC 120 V AC	
Mounting Type	Plug-in	
Number Of Poles	2P	
Circuit Breaker Type	Standard	
Ratings	HACR rated	
Electrical Connection	Box lugs	
Options	Shunt trip 120/208/240 V AC	

Complementary

Interrupt Rating10 kA 120/240 V AC 10 kA 120 V ACNumber Of Panel Spaces3Wire SizeAWG 4AWG 2/0 copper or aluminiumTightening Torque49.56 lbf.in (5.6 N.m)Height3.50 in (89 mm)Width2.24 in (57 mm)Depth2.91 in (74 mm)Net Weight0.98 lb(US) (0.445 kg)			
Wire Size AWG 4AWG 2/0 copper or aluminium Tightening Torque 49.56 lbf.in (5.6 N.m) Height 3.50 in (89 mm) Width 2.24 in (57 mm) Depth 2.91 in (74 mm)	Interrupt Rating		
Tightening Torque 49.56 lbf.in (5.6 N.m) Height 3.50 in (89 mm) Width 2.24 in (57 mm) Depth 2.91 in (74 mm)	Number Of Panel Spaces	3	
Height 3.50 in (89 mm) Width 2.24 in (57 mm) Depth 2.91 in (74 mm)	Wire Size	AWG 4AWG 2/0 copper or aluminium	
Width 2.24 in (57 mm) Depth 2.91 in (74 mm)	Tightening Torque	49.56 lbf.in (5.6 N.m)	
Depth 2.91 in (74 mm)	Height	3.50 in (89 mm)	
	Width	2.24 in (57 mm)	
Net Weight 0.98 lb(US) (0.445 kg)	Depth	2.91 in (74 mm)	
	Net Weight	0.98 lb(US) (0.445 kg)	

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE2A00104	
Discount Schedule	DE2A	
Gtin	785901030539	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Returnability	No	
Country Of Origin	US	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.30 in (5.842 cm)
Package 1 Width	3.40 in (8.636 cm)
Package 1 Length	3.80 in (9.652 cm)
Package 1 Weight	15.68 oz (444.521 g)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Product

Certifications & Standards

Reach Regulation	REACh Declaration	
Eu Rohs Directive	Compliant with Exemptions	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Circularity Profile	No need of specific recycling operations	
California Proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	