Product data sheet

Specification





Universal timing relay, Harmony Time, plug in, 0.1 s..60 mn, 24...240 V AC, 2 OC

RE88867305

! Discontinued on: Nov 22, 2021



Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Of Product	Zelio Time
Product Or Component Type	Universal timing relay
Discrete Output Type	Relay
Contacts Type And Composition	2 C/O
Width Pitch Dimension	1.38 in (35 mm)
Component Name	RE88867
Time Delay Type	Di W Ht At D B Ac A H
Time Delay Range	0.11 s 110 min 660 min 110 s 10100 h 660 s 110 h

Complementary

•	
Electrical Connection	Plug-in sub-base 11
Contacts Material	AgNi (cadmium free)
Line Rated Current	8 A
[Us] Rated Supply Voltage	24 V DC 24240 V AC 50/60 Hz
Voltage Range	0.851.1 Us
Housing Material	Self-extinguishing
Repeat Accuracy	+/- 0.5 % IEC 61812-1
Temperature Drift	+/- 0.05 %/°C
Voltage Drift	+/- 0.2 %/V
Setting Accuracy Of Time Delay	+/- 10 % of full scale 25 °C IEC 61812-1
Minimum Pulse Duration	100 ms under load 30 ms

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Maximum Reset Time	100 ms on de-energisation
On-Load Factor	100 %
Maximum Power Consumption	32 VA 240 V
Maximum Power Consumption	0.6 W 24 V 1.5 W 240 V
Breaking Capacity	2000 VA
Breaking Capacity	80 W
Minimum Switching Current	10 mA
Maximum Switching Current	8 A
Maximum Switching Voltage	250 V
Electrical Durability	100000 cycles 8 A, 250 V resistive
Mechanical Durability	5000000 cycles
[Uimp] Rated Impulse Withstand Voltage	5 kV 1.250 μs IEC 60664-1 5 kV 1.250 μs IEC 61812-1
Marking	CE
Creepage Distance	4 kV/3 IEC 60664-1
Surge Withstand	1 kV differential mode IEC 61000-4-5 level 3 2 kV common mode IEC 61000-4-5 level 3
Local Signalling	for flashing: timing in progress LED indicator (green) for on steady: relay energised, no timing in progress LED indicator (green) for pulsing: relay energised, no timing in progress (except functions Di-D) LED indicator (green)
Net Weight	0.18 lb(US) (0.08 kg)

Environment

Immunity To Microbreaks	10 ms
Dielectric Strength	2.5 kV 1 mA/1 minute 50 Hz IEC 61812-1
Standards	73/23/EEC EN 50081-1/2 89/336/EEC 93/68/EEC IEC 61812-1 IEC 60669-2-3 EN 50082-1/2
Product Certifications	CSA cURus GL
Ambient Air Temperature For Operation	-4140 °F (-2060 °C)
Ambient Air Temperature For Storage	-22140 °F (-3060 °C)
Ip Degree Of Protection	IP20 IEC 60529 terminal block) IP40 IEC 60529 housing) IP50 IEC 60529 front panel)
Vibration Resistance	0.35 mm 1055 Hz)IEC 60068-2-6
Relative Humidity	93 % without condensation IEC 60068-2-3
Resistance To Electrostatic Discharge	6 kV in contact IEC 61000-4-2 level 3 8 kV in air IEC 61000-4-2 level 3
Resistance To Electromagnetic Fields	9.14 V/m (10 V/m) 80 MHz to 1 GHz ENV 50140/204 level 3 9.14 V/m (10 V/m) 80 MHz to 1 GHz IEC 61000-4-3 level 3
Resistance To Fast Transients	1 kV IEC 61000-4-4 level 3 capacitive connecting clip) 2 kV IEC 61000-4-4 level 3 direct)

Immunity To Radioelectric Fields	10 V 0.1580 MHz)ENV 50141 (IEC 61000-4-6)
Immunity To Voltage Dips	30 % / 10 ms IEC 61000-4-11 60 % / 100 ms IEC 61000-4-11 95 % / 5 s IEC 61000-4-11
Disturbance Radiated/Conducted	Class B FN 55022 (FN 55011 group 1)

Ordering and shipping details

Category	US10CP222370
Discount Schedule	0CP2
Gtin	3389110278637
Returnability	No
Country Of Origin	FR

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.57 in (4 cm)
Package 1 Width	1.97 in (5 cm)
Package 1 Length	3.82 in (9.7 cm)
Package 1 Weight	3.00 oz (85 g)

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information


Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations

Dimensions Drawings

Width 35 mm




Product data sheet

RE88867305

Connections and Schema

Wiring Diagram



Technical Description

Function A : Power on Delay Relay


Description

The timing period T begins on energisation. After timing, the output(s) R close(s). The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs



Function Ac: On- and Off-Delay Relay with Control Signal

Description


After power-up, closing of the control contact C causes the timing period T to start (timing can be interrupted by operating the Gate control contact G). At the end of this timing period, the relay closes.

When control contact C re-opens, the timing T starts.


At the end of this timing period T, the output reverts to its initial position (timing can be interrupted by operating the Gate control contact G).

The second output can be either timed or instantaneous.

Function: 1 Output




Function: 2 Outputs



Function At: Power on Delay Relay (Summation) with Control Signal

Description

After power-up, the first opening of control contact C starts the timing. Timing can be interrupted each time control contact closes. When the cumulative total of time periods elapsed reaches the pre-set value T, the output relay closes.




T = t1 + t2 +...

Function B : Interval Relay with Control Signal

Description

10

After power-up, pulsing or maintaining control contact C starts the timing T. The output R closes for the duration of the timing period T then reverts to its initial state.




RE88867305

Function Bw : Double Interval Relay with Control Signal

Description

On closing and opening of control contact C, the output R closes for the duration of the timing period T.




Function C : Off-Delay Relay with Control Signal


Description

After power-up and closing of the control contact C, the output R closes. When control contact C re-opens, timing T starts. At the end of the timing period, the output(s) R revert(s) to its/their initial state. The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs




Function D : Symmetrical Flasher Relay (Starting Pulse Off)

Description


Repetitive cycle with two timing periods T of equal duration, with output(s) R changing state at the end of each timing period T.

The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs



Function Di : Symmetrical Flasher Relay (Starting Pulse On)

Description

Repetitive cycle with two timing periods T of equal duration, with output(s) R changing state at the end of each timing period T.


The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs

14



Function H : Interval Relay

Description


On energisation of the relay, timing period T starts and the output(s) R close(s). At the end of the timing period T, the output(s) R revert(s) to its/their initial state. The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs

Apr 26, 2024



2 timed outputs (R1/R2) or 1 timed output (R1) and 1 instantaneous output (R2 inst.)

15

Function Ht: Interval Relay (Summation) with Control Signal


Description

On energisation, the output R closes for the duration of a timing period T then reverts to its initial state.

Pulsing or maintaining control contact C will again close the output R.

Timing T is only active when control contact C is released and so the output R will not revert to its initial state until after a time t1 + t2 +...

The relay memorises the total, cumulative opening time of control contact C and, once the set time T is reached, the output R reverts to its initial state.



T = t1 + t2 +...

Legend

	Relay de-energised
	Relay energised
	Output open
	Output closed
С	Control contact
G	Gate
R	Relay or solid state output
R1/R2	2 timed outputs
R2 inst.	The second output is instantaneous if the right position is selected
Т	Timing period
Та -	Adjustable On-delay
Tr -	Adjustable Off-delay
U	Supply