# **Product data sheet**

Specification





# universal protection relay, PowerLogic P3U 3CT 1lo ringlug 4VT 16DI 8DO 48-230V DI110V RS485 ANSI

REL52055

Product availability: Stock - Normally stocked in distribution facility

Price\*: 2,313.15 USD

### Main

Range Of Product	PowerLogic P3
Product Or Component Type	Protection relay
Relay Application	Universal
Product Reference	P3U30-5AAA2BBAB
Mounting Case Size	30TE
Device Mounting	Flush
Mounting Mode	Flush mounting
Power Supply	48230 V AC/DC
Measuring Inputs	3 1/5 A CT phase current 1 1/5 A CT residual current 4 100 V/110 V VT voltage
Number Of Sensors	0 temperature sensor(s) 0 arc sensor(s)
Number Of Digital Inputs (Di)	16
Number Of Digital Outputs (Do)	8 DO 1 watchdog
Number Of Analogue Inputs	0
Number Of Analogue Outputs	0
Communication Ports	Front USB port 1 Rear RS485 1
Communication Protocols	IEC 60870-5-101 IEC 60870-5-103 DNP3 Modbus RTU DeviceNet SPAbus
Cybersecurity	Password protection Port hardening

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

#### **Protection Functions**

Phase overcurrent 50/51

Directional phase overcurrent 67

Earth fault overcurrent 50N/51N

Directional earth fault 67N Transient earth fault 67NI

Capacitor bank unbalance 51C

Broken conductor 46 I2/I1

Cold load pick-up

H2 detection 68H2

H5 detection 68H5 Breaker failure 50BF

Switch ON to fault (SOTF)

Directional active underpower 32

Fault locator 21FL

Recloser 79

Phase undercurrent 37

Excessive starting time, locked rotor 48/51LR

Motor restart inhibition 66

Capacitor overvoltage 59C

Negative sequence overcurrent 46

Overvoltage 59

Undervoltage 27

Positive sequence undervoltage 27P

Earth fault overvoltage 59N

Underfrequency 81/81N

Rate of change of frequency 81R

Synchro-check 25

Lockout relay 86

CT supervision 60 VT supervision 60 8

Programmable stages 99 8

Programmable curve

#### **Arc Flash Protection**

#### **Measurement Functions**

Current 3-phase

Current zero sequence

Current positive sequence

Current negative sequence

Current ratio of negative and positive

Voltage phase to earth

Voltage phase to phase

Voltage zero sequence

Voltage positive sequence Voltage negative sequence

Voltage ratio of negative and positive

Short circuit fault reactance

Fault location current

Earth fault reactance

Frequency

Active power

RMS active power

Reactive power

RMS reactive power

Apparent power

RMS apparent power

Active energy

Reactive energy

Cos o

Tan φ

Power angle

Power factor

Voltage phasor diagram view Current phasor diagram view

Current 2nd, 15th harmonics with THD

Voltage 2nd, 15th harmonics with THD Condition monitoring CB wear

Voltage interruption

#### **Control Functions**

Switchgear control and monitoring

Programmable switchgear interlocking

Local control on single-line diagram

Local control with I/O keys

Local/remote control

2 function keys

Mobile application with Easergy SmartApp

Web-server

Programmable logic

Controllable Switchgear Devices	4 controlled + 8 displayed
Number Of Setting Groups	4
Monitoring Functions	Trip circuit supervision 74 Circuit breaker monitoring Relay self-monitoring
Logs And Records	Event recording Disturbance recording Tripping context
Switchgear Diagnosis Type	CT supervision Trip circuit supervision TCS
Connections - Terminals	Screw removable (digital input/output) Ring lugs removable (current transformer) Pin removable (voltage transformer)

# Complementary

•	
Operating Threshold	110 V AC/DC
Software Name	ESetup Easergy Pro virtual simulation test Easergy SmartApp
Web Server	Embedded HTTP server
Display Type	LCD 128 x 64 pixels with single line diagram LCD 128 x 64 pixels with ANSI symbols
Number Of Key	2 customizable
Local Signalling	4 LEDs 8 LEDs programmable
Height	6.67 in (169.5 mm)
Width	6.69 in (170 mm)
Depth	8.07 in (205 mm)
Net Weight	5.51 lb(US) (2.5 kg) maximum

## **Environment**

Electromagnetic Compatibility	Emission toots IEC/EN 602EE 26 ad. 2
Electromagnetic Compatibility	Emission tests IEC/EN 60255-26 ed. 3
	Emission tests class A CISPR 11
	Emission tests class A CISPR 22
	EMC immunity IEC/EN 60255-26 ed. 3
	EMC immunity EN/IEC 61000-4-18
	EMC immunity IEC 60255-22-1
	EMC immunity level 4 EN/IEC 61000-4-2
	EMC immunity IEC 60255-22-2
	EMC immunity level 3 EN/IEC 61000-4-3
	EMC immunity IEC 60255-22-3
	EMC immunity level 4 EN/IEC 61000-4-4
	EMC immunity IEC 60255-22-4
	EMC immunity level 3 EN/IEC 61000-4-5
	EMC immunity IEC 60255-22-5
	EMC immunity level 3 EN/IEC 61000-4-6
	EMC immunity IEC 60255-22-6
	EMC immunity EN/IEC 61000-4-8
	EMC immunity level 5 EN/IEC 61000-4-9
	EMC immunity EN/IEC 61000-4-29
	EMC immunity EN/IEC 61000-4-11
	EMC immunity EN/IEC 61000-4-17
	EMC immunity IEC 60255-27
	EMC immunity class III IEC 60255-5
	EMC immunity EN/IEC 60255-1
Mechanical Robustness	Vibrations class II) IEC 60255-21-1
	VibrationsFc IEC 60068-2-6
	Shocks class II) IEC 60255-21-2
	ShocksEa IEC 60068-2-27

Seismic tests method A class II) IEC 60255-21-3

Climatic Withstand	Exposure to dry heat Bd EN/IEC 60068-2-2 Exposure to cold Ad EN/IEC 60068-2-1 Exposure to damp heat in service Db EN/IEC 60068-2-30 Exposure to damp heat in service Cab EN/IEC 60068-2-78
Ambient Air Temperature For Operation	-40149 °F (-4065 °C)
Ambient Air Temperature For Storage	-40158 °F (-4070 °C)
Ip Degree Of Protection	IP54 front IEC 60529
Relative Humidity	095 %, without condensation
Maximum Operating Altitude	6561.68 ft (2000 m)
Protective Treatment	Conformal coating

## Ordering and shipping details

Category	US1PL1S11405
Discount Schedule	PL1S
Gtin	3606481465450
Returnability	Yes
Country Of Origin	US

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.75 in (40 cm)
Package 1 Width	11.81 in (30 cm)
Package 1 Length	11.81 in (30 cm)
Package 1 Weight	8.38 lb(US) (3.8 kg)

## **Contractual warranty**

Warranty Up to 10 years (Standard warranty 2 years. Please check with your local SE

representative for extended warranty availability and conditions)



Green Premium<sup>TM</sup> label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Rohs Exemption Information

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information