## **Product data sheet**

Specifications







# Circuit breaker, PowerPacT R, 1000A, 3 pole, 600VAC, 65kA, busbar, Micrologic 3.0A, 80%

RKF36100U41A

#### Main

| Range                     | PowerPact       |  |
|---------------------------|-----------------|--|
| Product Name              | PowerPact R     |  |
| Product Or Component Type | Circuit breaker |  |
| Device Application        | Distribution    |  |

#### Complementary

| Complementary                             |  |  |
|---|--|--|
| Line Rated Current                        | 1000 A   |  |
| Number Of Poles                           | 3P   |  |
| Control Type                              | Operating handle   |  |
| Breaking Capacity Code                    | К  |  |
| Breaking Capacity                         | AIR 65 kA 240 V AC 50/60 Hz UL 489<br>AIR 65 kA 480 V AC 50/60 Hz UL 489<br>AIR 65 kA 600 V AC 50/60 Hz UL 489<br>Icu 85 kA 240 V AC 50/60 Hz IEC 60947-2<br>Icu 70 kA 380/415 V AC 50/60 Hz IEC 60947-2 |  |
| [Ue] Rated Operational Voltage            | 600 V AC 50/60 Hz UL 489   |  |
| Network Frequency                         | 50/60 Hz   |  |
| [Ics] Rated Service Breaking<br>Capacity  | 65 kA 240 V AC 50/60 Hz IEC 60947-2<br>55 kA 380/415 V AC 50/60 Hz IEC 60947-2   |  |
| [Uimp] Rated Impulse Withstand<br>Voltage | 8 kV IEC 60947-2   |  |
| Trip Unit Technology                      | Electronic, ammeter, MicroLogic 3.0 A, LI  |  |
| Continuous Current Rating                 | 80 %   |  |
| [Ui] Rated Insulation Voltage             | 750 V IEC 60947-2  |  |
| Trip Unit Name                            | MicroLogic 3.0 A   |  |
| Suitability For Isolation                 | Yes IEC 60947-2  |  |
| Utilisation Category                      | Category A   |  |
| Awg Gauge                                 | AWG 3/0750 kcmil aluminium/copper  |  |
| Local Signalling                          | Alarm 1 LED yellow)long-time pick up)<br>1 LED red)long-time pick up)<br>Trip causes 1 LED red)<br>1 LED red)digital ammeter)<br>Phase-loading LED green)load balancing)                                 |  |
| Mounting Mode                             | Unit mount busbar)   |  |
| Mounting Support                          | Busbar   |  |
| Electrical Connection                     | Busbar connection, line<br>Busbar connection, load   |  |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Terminal Identifier         | AL2500RK   |  |
|-----------------------------|--|--|
| Tightening Torque           | 601.85 lbf.in (68 N.m) 0.080.62 in² (50400 mm²) (AWG 1/0750 kcmil)<br>601.85 lbf.in (68 N.m) 0.080.23 in² (50150 mm²) (2 x AWG 1/02 x 300 kcmil) |  |
| Number Of Slots             | 2 auxiliary switch OF plug-in)<br>1 alarm switch SD plug-in)<br>1 voltage release MN or MX plug-in)  |  |
| Power Wire Stripping Length | 1.38 in (35 mm)  |  |
| Height                      | 16.24 in (412.50 mm)   |  |
| Width                       | 16.54 in (420.12 mm)   |  |
| Depth                       | 14.49 in (368.05 mm)   |  |
| Net Weight                  | 52 lb(US) (23.59 kg)   |  |
| Quantity Per Set            | 1  |  |
| Circuit Breaker Application | HACR rated   |  |

#### Environment

| Quality Labels                           | CE                                     |  |
|--|--|--|
| Standards                                | UL                                     |  |
|  | CSA                                    |  |
|  | NEMA                                   |  |
|  | NMX J-266                              |  |
|  | IEC 60947-2                            |  |
| Product Certifications                   | UL                                     |  |
|  | CSA                                    |  |
|  | NOM                                    |  |
| Ip Degree Of Protection                  | IP40                                   |  |
| Pollution Degree                         | 3 IEC 60947-1                          |  |
| Ambient Air Temperature For<br>Operation | -13158 °F (-2570 °C)                   |  |
| Ambient Air Temperature For<br>Storage   | -58185 °F (-5085 °C)                   |  |
| Operating Altitude                       | < 6561.68 ft (2000 m) without derating |  |
|  | 13123.36 ft (4000 m) with derating     |  |

## Ordering and shipping details

| Category          | 01245-RG,H,J,K,L,N UNIT MT BREAKERS |  |
|-------------------|-------------------------------------|--|
| Discount Schedule | DE2                                 |  |
| Returnability     | No                                  |  |
| Country Of Origin | US                                  |  |

## **Packing Units**

| -                            |                          |
|------------------------------|--------------------------|
| Unit Type Of Package 1       | PCE                      |
| Number Of Units In Package 1 | 1                        |
| Package 1 Height             | 16.22 in (41.2 cm)       |
| Package 1 Width              | 16.54 in (42.0 cm)       |
| Package 1 Length             | 14.49 in (36.8 cm)       |
| Package 1 Weight             | 52.00 lb(US) (23.587 kg) |

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free
Halogen Free Plastic Parts Product

#### **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Compliant with Exemptions   |
| China Rohs Regulation     | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information.  |
| Environmental Disclosure  | Product Environmental Profile   |
| Circularity Profile       | End of Life Information   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: DINP, which is<br>known to the State of California to cause cancer, and DIDP, which is known to the<br>State of California to cause birth defects or other reproductive harm. For more<br>information go to www.P65Warnings.ca.gov |