# Product data sheet

Specifications





power relay, Harmony electromechanical relays, DIN rail or panel mount relay, 30A, 2NO, 120V AC

RPF2AF7

Product availability: Stock - Normally stocked in distribution facility

Price\*: 12.69 USD

### Main

Range Of Product	Harmony Electromechanical Relays
Series Name	Power
Product Or Component Type	DIN rail/panel mount relay
Device Short Name	RPF
Contacts Type And Composition	2 NO
[Uc] Control Circuit Voltage	120 V AC 50/60 Hz
Control Type	Without lockable test button
Shape Of Pin	Flat
Contacts Material	Silver tin oxide
[Ithe] Conventional Enclosed Thermal Current	25 A -40131 °F (-4055 °C) relays side by side without a gap 30 A -40131 °F (-4055 °C) 13 mm gap between two relays
Resistive Rated Load	25 A 28 V DC 30 A 250 V AC
Utilisation Coefficient	10 %

### Complementary

Mounting Support	DIN rail Panel
Control Circuit Voltage Limits	96132 V
[le] Rated Operational Current	30 A 277 V AC) NO UL 20 A 28 V DC) NO UL 30 A 250 V AC) NO IEC 25 A 28 V DC) NO IEC
[Ui] Rated Insulation Voltage	250 V IEC 300 V UL
[Uimp] Rated Impulse Withstand Voltage	4 kV 1.2/50 μs
Maximum Switching Voltage	250 V IEC
Maximum Switching Capacity	7500 VA/700 W
Minimum Recommended Switching Capacity	6000 mW 500 mA / 12 V NO
Operating Rate	<= 1200 cycles/hour under load <= 18000 cycles/hour no-load
Mechanical Durability	5000000 cycles

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Electrical Durability	100000 cycles resistive
Average Coil Consumption	4 VA 60 Hz
Drop-Out Voltage Threshold	>= 0.15 Uc
Operate Time	25 ms
Release Time	25 ms
Average Resistance	4250 Ohm at 68 °F (20 °C) +/- 15 %
Safety Reliability Data	B10d = 100000
Protection Category	RT II
Test Levels	Level A group mounting
Operating Position	Any position
Cad Overall Width	1.33 in (33.7 mm)
Cad Overall Height	2.70 in (68.5 mm)
Cad Overall Depth	1.54 in (39.2 mm)
Net Weight	0.18 lb(US) (0.082 kg)
Device Presentation	Complete product

## **Environment**

Dielectric Strength	2000 V AC between poles with basic 4000 V AC between coil and contact with reinforced 1500 V AC between contacts with micro disconnection
Standards	CSA C22.2 No 14 UL 508 IEC 61810-1
Product Certifications	UL CSA GOST CE
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)
Ambient Air Temperature For Operation	-40131 °F (-4055 °C)
Vibration Resistance	3 gn +/- 1 mm 10150 Hz)5 cycles in operation 10 gn +/- 1 mm 10150 Hz)5 cycles not operating
Ip Degree Of Protection	IP40 conforming to IEC 60529
Shock Resistance	10 gnin operation 30 gnnot operating
Pollution Degree	3

# Ordering and shipping details

Category	US10CP221127
Discount Schedule	0CP2
Gtin	3389119401548
Returnability	Yes
Country Of Origin	CN

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	1.73 in (4.4 cm)
Package 1 Width	1.33 in (3.37 cm)
Package 1 Length	2.70 in (6.85 cm)
Package 1 Weight	3.26 oz (92.5 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	1.97 in (5 cm)
Package 2 Width	5.59 in (14.2 cm)
Package 2 Length	7.83 in (19.9 cm)
Package 2 Weight	32.63 oz (925 g)
Unit Type Of Package 3	S02
Number Of Units In Package 3	60
Package 3 Height	5.91 in (15 cm)
Package 3 Width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	13.56 lb(US) (6.15 kg)

# **Contractual warranty**

Warranty 18 months

# Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes


### **Certifications & Standards**


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
	<u> </u>
Circularity Profile	No need of specific recycling operations

### RPF2AF7

#### **Dimensions Drawings**

#### **Dimensions**






### RPF2AF7

Connections and Schema

### Wiring Diagram




Symbols shown in blue correspond to Nema marking.

#### Performance Curves

### **Electrical Durability of Contacts**

#### **AC Resistive load**




X Switching capacity (kVA)

Y Durability (number of operating cycles)


#### AC Reduction coefficient for inductive load (depending on power factor $\cos \phi$ )

Durability (inductive load) = durability (resistive load) x reduction coefficient.



Y reduction coefficient

#### Maximum switching capacity on DC resistive load



**A** 30 A **B** 25 A

Note: These are typical curves, actual durability depends on load, environment, duty cycle, etc.