Product data sheet

Specification





plug-in relay, Harmony electromechanical relays, 15A, 2CO, with LED, lockable test button, 24V DC

RPM22BD

Product availability: Stock - Normally stocked in distribution facility

Price*: 8.30 USD

Main

| Range Of Product | Harmony Electromechanical Relays |
|---|----------------------------------|
| Series Name | Power |
| Product Or Component Type | Plug-in relay |
| Device Short Name | RPM |
| Contacts Type And Composition | 2 C/O |
| [Uc] Control Circuit Voltage | 24 V DC |
| [Ithe] Conventional Enclosed Thermal Current | 15 A -40131 °F (-4055 °C) |
| Status Led | With |
| Control Type | Lockable test button |
| Utilisation Coefficient | 20 % |

Complementary

| Shape Of Pin | Flat |
|--|--------------------------------|
| [Ui] Rated Insulation Voltage | 250 V IEC |
| | 300 V CSA |
| | 300 V UL |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV 1.2/50 μs |
| Contacts Material | AgNi |
| [le] Rated Operational Current | 15 A 277 V AC) UL |
| | 15 A 28 V DC) UL |
| | 15 A 250 V AC) NO IEC |
| | 15 A 28 V DC) NO IEC |
| | 7.5 A 250 V AC) NC IEC |
| | 7.5 A 28 V DC) NC IEC |
| Maximum Switching Voltage | 250 V IEC |
| Resistive Load Current | 15 A 250 V AC |
| | 15 A 28 V DC |
| Maximum Switching Capacity | 3750 VA |
| , | 420 W |
| Minimum Switching Capacity | 170 mW 10 mA, 17 V |
| Operating Rate | <= 1200 cycles/hour under load |
| | <= 18000 cycles/hour no-load |
| Mechanical Durability | 10000000 cycles |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Electrical Durability | 100000 cycles resistive | |
|----------------------------------|-----------------------------------|--|
| Average Coil Consumption | 0.85 W | |
| Drop-Out Voltage Threshold | >= 0.1 Uc DC | |
| Operate Time | 20 ms at nominal voltage | |
| Release Time | 20 ms at nominal voltage | |
| Average Coil Resistance | 640 Ohm at 68 °F (20 °C) +/- 10 % | |
| Rated Operational Voltage Limits | 19.226.4 V DC | |
| Protection Category | RTI | |
| Test Levels | Level A group mounting | |
| Operating Position | Any position | |
| Pollution Degree | 3 | |
| Safety Reliability Data | B10d = 100000 | |
| Net Weight | 0.08 lb(US) (0.036 kg) | |
| Device Presentation | Complete product | |

Environment

| Dielectric Strength | 1500 V AC between contacts with micro disconnection 2000 V AC between coil and contact with reinforced 2000 V AC between poles with basic | |
|---------------------------------------|---|--|
| Standards | CSA C22.2 No 14 IEC 61810-1 UL 508 | |
| Product Certifications | EAC UL CSA | |
| Ambient Air Temperature For Storage | -40185 °F (-4085 °C) | |
| Ambient Air Temperature For Operation | -40131 °F (-4055 °C) | |
| Vibration Resistance | 3 gn +/- 1 mm 10150 Hz)5 cycles in operation 5 gn +/- 1 mm 10150 Hz)5 cycles not operating | |
| Degree Of Protection (Housing Only) | IP40 conforming to IEC 60529 | |
| Shock Resistance | 15 gnin operation 30 gnnot operating | |

Ordering and shipping details

| Category | US10CP221127 | |
|-------------------|---------------|--|
| Discount Schedule | 0CP2 | |
| Gtin | 3389119401890 | |
| Returnability | Yes | |
| Country Of Origin | US | |

Packing Units

| Unit Type Of Package 1 | PCE | |
|------------------------------|------------------|--|
| Number Of Units In Package 1 | 1 | |
| Package 1 Height | 1.85 in (4.7 cm) | |
| Package 1 Width | 0.83 in (2.1 cm) | |

| Package 1 Length | 1.10 in (2.8 cm) |
|------------------------------|--------------------------|
| Package 1 Weight | 1.41 oz (40 g) |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 1.26 in (3.2 cm) |
| Package 2 Width | 4.06 in (10.3 cm) |
| Package 2 Length | 4.96 in (12.6 cm) |
| Package 2 Weight | 14.39 oz (408 g) |
| Unit Type Of Package 3 | S02 |
| Number Of Units In Package 3 | 240 |
| Package 3 Height | 5.91 in (15 cm) |
| Package 3 Width | 11.81 in (30 cm) |
| Package 3 Length | 15.75 in (40 cm) |
| Package 3 Weight | 22.84 lb(US) (10.362 kg) |

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes


Certifications & Standards


| Reach Regulation | REACh Declaration |
|---------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | No need of specific recycling operations |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Dimensions Drawings

Dimensions








Pin Side View






RPM22BD

Connections and Schema

Wiring Diagram






Symbols shown in blue correspond to Nema marking.

RPM22BD

Performance Curves

Electrical Durability of Contacts


Durability (inductive load) = durability (resistive load) x reduction coefficient. Resistive AC load



X Switching capacity (kVA)


Y Durability (Number of operating cycles)

Reduction coefficient for inductive AC load (depending on power factor cos φ)



Y Reduction coefficient (A)

Maximum switching capacity on resistive DC load



X Voltage DC

Y Current DC

Note: These are typical curves, actual durability depends on load, environment, duty cycle, etc.