Product data sheet

Specifications





servo motor SH3 055 1,05Nm,nokey,single,nobrake, 90°conn.IP54/IP65,9k RPM

SH30553P01A2000

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1,171.90 USD

Main

Range Compatibility	PacDrive 3	
Product Or Component Type	Servo motor	
Device Short Name	SH3P	

Complementary

complementary	
Maximum Mechanical Speed	9000 rpm
[Us] Rated Supply Voltage	115480 V
Phase	Three phase
Continuous Stall Current	1.7 A
Continuous Stall Torque	9.29 lbf.in (1.05 N.m) 115480 V three phase
Continuous Power	680 W
Peak Stall Torque	30.98 lbf.in (3.5 N.m) 115480 V three phase
Nominal Output Power	240 W 115 V single phase 460 W 230 V single phase 880 W 400 V three phase 970 W 480 V three phase
Nominal Torque	10.00 lbf.in (1.13 N.m) 115 V single phase 9.74 lbf.in (1.1 N.m) 230 V single phase 7.17 lbf.in (0.81 N.m) 400 V three phase 7.17 lbf.in (0.81 N.m) 480 V three phase
Nominal Speed	4000 rpm 230 V single phase 9000 rpm 480 V three phase 2000 rpm 115 V single phase 8000 rpm 400 V three phase
Maximum Current Irms	6.5 A
Shaft End	Smooth shaft
Shaft Diameter	0.35 in (9 mm)
Shaft Length	0.79 in (20 mm)
Ip Degree Of Protection	IP54 shaft bushing without shaft seal ring: conforming to EN/IEC 60034-5 IP65 motor: conforming to EN/IEC 60034-5 IP65 shaft bushing: conforming to EN/IEC 60034-5
Encoder Type	Absolute single turn SinCos Hiperface
Speed Feedback Resolution	128 periods
Holding Brake	Without
Mounting Support	International standard flange

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Motor Flange Size	2.17 in (55 mm)	
Electrical Connection	Rotatable right angled connector	
Torque Constant	0.62 N.m/A 248 °F (120 °C)	
Back Emf Constant	41 V/krpm 68 °F (20 °C)	
Number Of Motor Poles	3	
Rotor Inertia	0.134 kg.cm ²	
Stator Resistance	10.4 Ohm	
Stator Inductance	37.98 mH	
Maximum Radial Force Fr	190 N 8000 rpm 390 N 1000 rpm 310 N 2000 rpm 270 N 3000 rpm 240 N 4000 rpm 230 N 5000 rpm 210 N 6000 rpm 200 N 7000 rpm	
Maximum Axial Force Fa	40 N	
Type Of Cooling	Natural convection	
Length	6.95 in (176.5 mm)	
Centring Collar Diameter	1.57 in (40 mm)	
Centring Collar Depth	0.08 in (2 mm)	
Number Of Mounting Holes	4	
Mounting Holes Diameter	0.22 in (5.5 mm)	
Circle Diameter Of The Mounting Holes	2.48 in (63 mm)	
Net Weight	3.97 lb(US) (1.8 kg)	

Ordering and shipping details

Category	US1PC5218359	
Discount Schedule	PC52	
Gtin	3606485295411	
Returnability	No	
Country Of Origin	US	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.53 in (11.5 cm)
Package 1 Width	7.48 in (19.0 cm)
Package 1 Length	15.55 in (39.5 cm)
Package 1 Weight	4.85 lb(US) (2.2 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov