# **Product data sheet**

Specifications





### servo motor SH3 100 2,94Nm,nokey,single,brake, 90°conn.IP54/IP65,6k RPM

SH31001P01F2000

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 1,592.81 USD

### Main

Range Compatibility	PacDrive 3
Product Or Component Type	Servo motor
Device Short Name	SH3P

### Complementary

Maximum Mechanical Speed	6000 rpm
[Us] Rated Supply Voltage	115480 V
Phase	Three phase
Continuous Stall Current	3.5 A
Continuous Stall Torque	26.02 lbf.in (2.94 N.m) 115480 V three phase
Continuous Power	1190 W
Peak Stall Torque	84.97 lbf.in (9.6 N.m) 115480 V three phase
Nominal Output Power	410 W 115 V single phase 790 W 230 V single phase 1410 W 400 V three phase 1630 W 480 V three phase
Nominal Torque	25.76 lbf.in (2.91 N.m) 115 V single phase 23.37 lbf.in (2.64 N.m) 230 V single phase 20.09 lbf.in (2.27 N.m) 400 V three phase 20.09 lbf.in (2.27 N.m) 480 V three phase
Nominal Speed	1250 rpm 115 V single phase 2500 rpm 230 V single phase 5000 rpm 400 V three phase 6000 rpm 480 V three phase
Maximum Current Irms	12 A
Shaft End	Smooth shaft
Shaft Diameter	0.75 in (19 mm)
Shaft Length	1.57 in (40 mm)
Ip Degree Of Protection	IP54 shaft bushing without shaft seal ring: conforming to EN/IEC 60034-5 IP65 motor: conforming to EN/IEC 60034-5 IP65 shaft bushing: conforming to EN/IEC 60034-5
Encoder Type	Absolute single turn SinCos Hiperface
Speed Feedback Resolution	128 periods
Holding Brake	With
Holding Torque	79.66 lbf.in (9 N.m)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting Support	International standard flange	
Motor Flange Size	3.94 in (100 mm)	
Electrical Connection	Rotatable right angled connector	
Torque Constant	0.84 N.m/A 248 °F (120 °C)	
Back Emf Constant	60 V/krpm 68 °F (20 °C)	
Number Of Motor Poles	4	
Rotor Inertia	2.018 kg.cm²	
Stator Resistance	3.8 Ohm	
Stator Inductance	27.15 mH	
Maximum Radial Force Fr	900 N 1000 rpm 720 N 2000 rpm 630 N 3000 rpm 570 N 4000 rpm 530 N 5000 rpm	
Maximum Axial Force Fa	160 N	
Type Of Cooling	Natural convection	
Length	7.85 in (199.5 mm)	
Centring Collar Diameter	3.74 in (95 mm)	
Centring Collar Depth	0.14 in (3.5 mm)	
Number Of Mounting Holes	4	
Mounting Holes Diameter	0.35 in (9.0 mm)	
Circle Diameter Of The Mounting Holes	4.53 in (115 mm)	
Net Weight	10.58 lb(US) (4.8 kg)	

# Ordering and shipping details

Category	US1PC5218359
Discount Schedule	PC52
Gtin	3606485296401
Returnability	No
Country Of Origin	US

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.27 in (21.0 cm)
Package 1 Width	7.09 in (18.0 cm)
Package 1 Length	14.02 in (35.6 cm)
Package 1 Weight	12.83 lb(US) (5.821 kg)

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov