# Product data sheet

Specifications





# servo motor SH3 100 2,94Nm,nokey,multi,nobrake,str.con n,IP65/IP65,6k RPM

SH31001P02A1100

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Price\*: 1,571.89 USD

#### Main

Range Compatibility	PacDrive 3	
Product Or Component Type	Servo motor	
Device Short Name	SH3P	

#### Complementary

oompicinental y		
Maximum Mechanical Speed	6000 rpm	
[Us] Rated Supply Voltage	115480 V	
Phase	Three phase	
Continuous Stall Current	3.5 A	
Continuous Stall Torque	26.02 lbf.in (2.94 N.m) 115480 V three phase	
Continuous Power	1190 W	
Peak Stall Torque	84.97 lbf.in (9.6 N.m) 115480 V three phase	
Nominal Output Power	410 W 115 V single phase 790 W 230 V single phase 1410 W 400 V three phase 1630 W 480 V three phase	
Nominal Torque	25.76 lbf.in (2.91 N.m) 115 V single phase 23.37 lbf.in (2.64 N.m) 230 V single phase 20.09 lbf.in (2.27 N.m) 400 V three phase 20.09 lbf.in (2.27 N.m) 480 V three phase	
Nominal Speed	1250 rpm 115 V single phase 2500 rpm 230 V single phase 5000 rpm 400 V three phase 6000 rpm 480 V three phase	
Maximum Current Irms	12 A	
Shaft End	Smooth shaft	
Shaft Diameter	0.75 in (19 mm)	
Shaft Length	1.57 in (40 mm)	
Ip Degree Of Protection	IP65 motor: conforming to EN/IEC 60034-5 IP65 shaft bushing: conforming to EN/IEC 60034-5	
Encoder Type	Absolute multitum SinCos Hiperface	
Speed Feedback Resolution	128 periods	
Holding Brake	Without	
Mounting Support	International standard flange	
Motor Flange Size	3.94 in (100 mm)	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Electrical Connection	Straight connector	
Torque Constant	0.84 N.m/A 248 °F (120 °C)	
Back Emf Constant	60 V/krpm 68 °F (20 °C)	
Number Of Motor Poles	4	
Rotor Inertia	1.4 kg.cm <sup>2</sup>	
Stator Resistance	3.8 Ohm	
Stator Inductance	27.15 mH	
Maximum Radial Force Fr	900 N 1000 rpm 720 N 2000 rpm 630 N 3000 rpm 570 N 4000 rpm 530 N 5000 rpm	
Maximum Axial Force Fa	160 N	
Type Of Cooling	Natural convection	
Length	6.63 in (168.5 mm)	
Centring Collar Diameter	3.74 in (95 mm)	
Centring Collar Depth	0.14 in (3.5 mm)	
Number Of Mounting Holes	4	
Mounting Holes Diameter	0.35 in (9.0 mm)	
Circle Diameter Of The Mounting Holes	4.53 in (115 mm)	
Net Weight	9.48 lb(US) (4.3 kg)	

# Ordering and shipping details

Category	US1PC5218359	
Discount Schedule	PC52	
Gtin	3606481972200	
Returnability	No	
Country Of Origin	US	

## **Packing Units**

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Weight	9.46 lb(US) (4.291 kg)	

## **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov