Product data sheet

Specifications





Switch disconnector, TeSys Control, for ON/emergency stop, 20A(VN20), for mounting on door

VCDN20

Product availability: Stock - Normally stocked in distribution facility

Price*: 102.00 USD

Main

Range	TeSys
Product Name	TeSys Mini-VARIO
Device Short Name	VCDN
Product Or Component Type	Emergency stop switch disconnector
Performance Level	Standard
Poles Description	3P
Contacts Type And Composition	3 NO
Network Type	DC AC
Control Type	Rotary handle
Rotary Handle Mounting Style	Direct
Handle Colour	Red
Handle Front Plate Colour	Yellow
Rotary Handle Padlocking	1 to 3 padlocks 0.160.31 in (48 mm)

Complementary

Marking	0 - 1
Mounting Support	Handle door
	Switch door
Fixing Mode	Hole 0.89 in (22.5 mm) handle
[Ith] Conventional Free Air Thermal Current	20 A
[Ithe] Conventional Enclosed Thermal Current	16 A
[Ie] Rated Operational Current	11 A AC-23)400 V
Rated Operational Power In W	4 kW 230240 V AC-23A)
	5.5 kW 400415 V AC-23A)
	7.5 kW 500 V AC-23A)
	11 kW 690 V AC-23A)
	3 kW 230240 V AC-3)
	4 kW 400415 V AC-3)
	5.5 kW 500 V AC-3)
	5.5 kW 690 V AC-3)
Intermittent Duty Class	30
Making Capacity (I Rms)	200 A 400 V AC-21A
	200 A 400 V AC-22A
	200 A 400 V AC-23A

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

[Icm] Rated Short-Circuit Making Capacity	0.5 kA 400 V at Ipeak
[Icw] Rated Short-Time Withstand Rms Current	140 A 400 V 1 s
Rated Conditional Short-Circuit	6 kA 400 V 20 A aM
Current	6 kA 400 V 20 A gG
Breaking Capacity	200 kA 400 V AC-21A)
	200 kA 400 V AC-22A)
	200 kA 400 V AC-23A)
Device Composition	Handle
	Switch
Mechanical Durability	50000 cycles
Electrical Durability	30000 cycles DC-15
	50000 cycles AC-21
Suitability For Isolation	Yes
Connections - Terminals	Power circuit screw clamp terminals 0.01 in ² (4 mm ²) flexible - with cable end
	Power circuit screw clamp terminals 0.01 in ² (4 mm ²) solid
Tightening Torque	Power circuit 6.20 lbf.in (0.7 N.m) screw clamp terminals
Handle Front Plate Dimension	60 x 60 mm
Height	2.36 in (60 mm)
Width	2.36 in (60 mm)
Net Weight	0.39 lb(US) (0.177 kg)

Environment

Standards	IEC 60947-3
Product Certifications	GL CSA UL CCC UKCA
Protective Treatment	TC
Ip Degree Of Protection	IP65
Mechanical Robustness	Shocks 11 ms 15 gn) IEC 60068-2-27 Vibrations 10150 Hz 1 gn) IEC 60068-2-6

Ordering and shipping details

Category	US10CP121730
Discount Schedule	0CP1
Gtin	3389110759914
Returnability	Yes
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.11 in (7.9 cm)
Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	4.72 in (12.0 cm)
Package 1 Weight	6.46 oz (183.0 g)

Unit Type Of Package 2	S03
Number Of Units In Package 2	24
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	10.73 lb(US) (4.865 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov