Product data sheet

Specification





module XPSAC - Emergency stop - 24 V AC DC

XPSAC5121

- Discontinued on: Dec 31, 2022
- ! To be end-of-service on: Dec 31, 2024



Product availability: Stock - Normally stocked in distribution facility

Main

Range Of Product	Preventa Safety automation
Product Or Component Type	Preventa safety module
Safety Module Name	XPSAC
Safety Module Application	For emergency stop and switch monitoring
Function Of Module	Emergency stop Switch monitoring
Safety Level	Can reach PL e/category 4 EN/ISO 13849-1 Can reach SILCL 3 EN/IEC 62061
Safety Reliability Data	MTTFd = 210.4 years EN/ISO 13849-1 DC > 99 % EN/ISO 13849-1 PFHd = 3.56E-9 1/h EN/IEC 62061
Type Of Start	Unmonitored
Connections - Terminals	Captive screw clamp terminals, 1 x 0.141 x 2.5 mm² flexible without cable end Captive screw clamp terminals, 1 x 0.141 x 2.5 mm² solid without cable end Captive screw clamp terminals, 1 x 0.251 x 1.5 mm² flexible with cable end, with bezel Captive screw clamp terminals, 1 x 0.251 x 2.5 mm² flexible with cable end, without bezel Captive screw clamp terminals, 2 x 0.142 x 0.75 mm² flexible without cable end Captive screw clamp terminals, 2 x 0.142 x 0.75 mm² solid without cable end Captive screw clamp terminals, 2 x 0.252 x 1 mm² flexible with cable end, without bezel Captive screw clamp terminals, 2 x 0.52 x 1.5 mm² flexible with cable end, with double bezel
Output Type	Relay instantaneous opening, 3 NO, volt-free
Number Of Additional Circuits	1 solid state output
[Us] Rated Supply Voltage	24 V AC - 2010 % 24 V DC - 2020 %

Complementary

Supply Frequency	50/60 Hz
Maximum Power Consumption In W	1.2 W DC
Maximum Power Consumption In Va	2.5 VA AC
[Uc] Control Circuit Voltage	24 V
Breaking Capacity	180 VA holding AC-15 C300 relay output 1800 VA inrush AC-15 C300 relay output
Breaking Capacity	1.5 A 24 V DC-13)50 ms relay output

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Output Thermal Current	6 A per relay relay output
[Ith] Conventional Free Air Thermal Current	10.5 A
Associated Fuse Rating	4 A gG or gL relay output EN/IEC 60947-5-1, DIN VDE 0660 part 200 6 A fast blow relay output EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum Output Current	10 mA relay output
Minimum Output Voltage	16 V relay output
Maximum Response Time On Input Open	100 ms
[Ui] Rated Insulation Voltage	300 V 2)IEC 60947-5-1 300 V 2)DIN VDE 0110 part 1
[Uimp] Rated Impulse Withstand Voltage	4 kV III IEC 60947-5-1 4 kV III DIN VDE 0110 part 1
Local Signalling	2 LEDs
Current Consumption	40 mA 24 V DC on power supply 90 mA 24 V AC on power supply
Mounting Support	35 mm symmetrical DIN rail
Net Weight	0.35 lb(US) (0.16 kg)

Environment

Standards	EN/IEC 60947-5-1 EN/ISO 13850 EN 60204-1 EN 1088/ISO 14119
Product Certifications	UL CSA TÜV
Ip Degree Of Protection	IP20 terminals)EN/IEC 60529 IP40 enclosure)EN/IEC 60529
Ambient Air Temperature For Operation	14131 °F (-1055 °C)
Ambient Air Temperature For Storage	-13185 °F (-2585 °C)

Ordering and shipping details

Category	US1SAF222477
Discount Schedule	SAF2
Gtin	3389110274011
Returnability	Yes
Country Of Origin	ID

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.18 in (3.000 cm)
Package 1 Width	4.09 in (10.400 cm)
Package 1 Length	4.72 in (12.000 cm)
Package 1 Weight	6.91 oz (196.000 g)
Unit Type Of Package 2	S01
Number Of Units In Package 2	16

Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	5.91 in (15.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	7.67 lb(US) (3.478 kg)
Unit Type Of Package 3	P06
Number Of Units In Package 3	512
Package 3 Height	29.53 in (75.000 cm)
Package 3 Width	23.62 in (60.000 cm)
Package 3 Length	31.50 in (80.000 cm)
Package 3 Weight	254.72 lb(US) (115.540 kg)

Contractual warranty

Warranty 18 months

Sustainability Screen Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >


Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information

Product data sheet

XPSAC5121

Dimensions Drawings

Dimensions

