Product data sheet

Specifications



green light block with body/fixing collar with integral LED 230...240V

() Discontinued on: Dec 2, 2020

(!) End-of-service on: Dec 31, 2020

Main

| Range Of Product | Harmony XB4 |
|-------------------------------|--|
| Product Or Component Type | Complete body/contact assembly and light block |
| Device Short Name | ZB4 |
| Fixing Collar Material | Zamak |
| Sale Per Indivisible Quantity | 1 |
| Head Type | Standard |
| Contacts Type And Composition | 1 NO |
| Contact Operation | Slow-break |
| Connections - Terminals | Plug-in connector |
| Light Source | Protected LED |
| Bulb Base | Integral LED |
| Light Block Supply | Direct |
| Light Source Colour | Green |
| [Us] Rated Supply Voltage | 230240 V AC 50/60 Hz |

Complementary

| Cad Overall Width | 1.18 in (30 mm) |
|--|--|
| Cad Overall Height | 1.85 in (47 mm) |
| Terminals Description Iso N°1 | (13-14)NO |
| Contacts Usage | Standard |
| Positive Opening | Without |
| Operating Travel | 0.10 in (2.6 mm) NO changing electrical state) 0.17 in (4.3 mm) total travel) |
| Operating Force | 2.3 N NO changing electrical state |
| Operating Torque | 0.44 lbf.in (0.05 N.m) NO changing electrical state |
| Mechanical Durability | 5000000 cycles |
| Contacts Material | Silver alloy (Ag/Ni) |
| Short-Circuit Protection | 4 A cartridge fuse gG EN/IEC 60947-5-1 |
| [Ith] Conventional Free Air Thermal Current | 10 A EN/IEC 60947-5-1 |
| [Ui] Rated Insulation Voltage | 250 V 3)EN/IEC 60947-1 |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| [Uimp] Rated Impulse Withstand Voltage | 4 kV EN 60947-1 |
|---|--|
| [le] Rated Operational Current | 3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 6 A 120 V, AC-15, A300 EN/IEC 60947-5-1 0.1 A 250 V, DC-13, R300 EN/IEC 60947-5-1 0.22 A 125 V, DC-13, R300 EN/IEC 60947-5-1 |
| Electrical Durability | 1000000 cycles, AC-15, 1 A 230 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 1.5 A 120 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C 1000000 cycles, AC-15, 3 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.15 A 110 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C 1000000 cycles, DC-13, 0.4 A 24 V 3600 cyc/h 0.5 EN/IEC 60947-5-1 appendix C |
| Electrical Reliability | Λ < 10exp(-6) 5 V 1 mA in clean environment EN/IEC 60947-5-4 Λ < 10exp(-8) 17 V 5 mA in clean environment EN/IEC 60947-5-4 |
| Signalling Type | Steady |
| Supply Voltage Limits | 195264 V AC |
| Current Consumption | 14 mA |
| Service Life | 100000 h at rated voltage and 25 °C |
| Surge Withstand | 1 kV IEC 61000-4-5 |

Environment

| Protective Treatment | тн |
|--|---|
| Ambient Air Temperature For Storage | -40158 °F (-4070 °C) |
| Ambient Air Temperature For Operation | -40158 °F (-4070 °C) |
| Electrical Shock Protection Class | Class I IEC 60536 |
| Standards | JIS C8201-5-1 EN/IEC 60947-5-4 UL 508 EN/IEC 60947-5-5 EN/IEC 60947-1 EN/IEC 60947-5-1 CSA C22.2 No 14 JIS C8201-1 |
| Product Certifications | LROS (Lloyds register of shipping) GL DNV BV UL Listed CSA |
| Vibration Resistance | 5 gn 2500 Hz)IEC 60068-2-6 |
| Shock Resistance | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 |
| Resistance To Fast Transients | 2 kV IEC 61000-4-4 |
| Resistance To Electromagnetic Fields | 9.14 V/m (10 V/m) IEC 61000-4-3 |
| Resistance To Electrostatic Discharge | 6 kV on contact (on metal parts) IEC 61000-2-6 8 kV in free air (in insulating parts) IEC 61000-2-6 |
| Electromagnetic Emission | Class B IEC 55011 |

Ordering and shipping details

Gtin

3389110894479

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information
Yes


Certifications & Standards

| Reach Regulation | REACh Declaration |
|-----------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| | |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Weee Circularity Profile | |

Product data sheet

Dimensions Drawings

Dimensions



Product data sheet ZB4BW0M314

Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

