

modular digital ammeter iAMP - 230V - 0..10A

15202

Main

Range	Acti9	
Device Short Name	iAMP	
Product Or Component Type	Ammeter	
Range Compatibility	Prisma Prisma P door Prisma Prisma G door	
Network Type	AC 50/60 Hz	
Mounting Support	DIN rail	

Complementary

Type Of Measurement	Current
[Us] Rated Supply Voltage	230 AC at 50/60 Hz
Power Consumption In Va	0.3 VA
Power Consumption In Va	0.3 VA
9 Mm Pitches	4
Width	36 mm
Height	87 mm
Depth	65 mm
Connections - Terminals	Tunnel type terminal 2 cable(s) 2.5 mm²

Environment

Standards	EN 50081-1 IEC 61010-1 EN 50082-1
Ambient Air Temperature For Operation	-2050 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	8.0 cm
Package 1 Length	9.2 cm
Package 1 Weight	187.0 g
Unit Type Of Package 2	S02

Number Of Unite In Beakage 2	20
Number Of Units In Package 2	36
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.102 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Read	ch Regulation	REACh Declaration
Eu F	Rohs Directive	Compliant EU RoHS Declaration
Chin	na Rohs Regulation	China RoHS declaration
Wee	е	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins