Product datasheet

Specification





base unit S10UD for Sepam series 20 - 24...250 V - with advanced UMI

59607

Main

Local Signalling

| Range Of Product | Sepam series 20 |
|-----------------------------|---|
| Device Short Name | S10UD |
| User Machine Interface Type | Advanced |
| Complementary | |
| Umi Indication | Metering and diagnosis data Status of logic imputs Alarms and operating messages Protection setting Sepam parameter setting Version of Sepam and remote modules |
| Umi Control | Alarm acknowledgement Output testing Sepam reset |
| Display Resolution | 128 x 64 pixels |
| Number Of Key | 9 |

2 LEDs for Sepam operating status (front face) 9 LEDs for indication of parameters (front face)

| Output Type | Annunciation relay: 100240 V AC 47.563 Hz continuous current: 2 A breaking |
|--|---|
| | capacity: 1 A $\cos \varphi > 0.3$ |
| | Annunciation relay: 127 V DC continuous current: 2 A breaking capacity: 0.5 A L/R < 20 ms |
| | Annunciation relay: 220 V DC continuous current: 2 A breaking capacity: 0.15 A L/R < 20 ms |
| | Annunciation relay: 24 V DC continuous current: 2 A breaking capacity: 2 A L/R < 20 ms |
| | Annunciation relay: 48 V DC continuous current: 2 A breaking capacity: 1 A L/R < 20 ms |
| | Control relay: 100240 V AC 47.563 Hz continuous current: 8 A breaking capacity: |
| | 5 A cos φ > 0.3 making capacity: < 15 A for 200 ms Control relay: 100240 V AC 47.563 Hz continuous current: 8 A breaking capacity: |
| | 8 A resistive making capacity: < 15 A for 200 ms Control relay: 127 V DC continuous current: 8 A breaking capacity: 0.2 A L/R < 40 ms making capacity: < 15 A for 200 ms |
| | Control relay: 127 V DC continuous current: 8 A breaking capacity: 0.5 A L/R < 20 ms making capacity: < 15 A for 200 ms |
| | Control relay: 127 V DC continuous current: 8 A breaking capacity: 0.7 A resistive making capacity: < 15 A for 200 ms |
| | Control relay: 220 V DC continuous current: 8 A breaking capacity: 0.1 A L/R < 40 ms making capacity: < 15 A for 200 ms |
| | Control relay: 220 V DC continuous current: 8 A breaking capacity: 0.2 A L/R < 20 ms making capacity: < 15 A for 200 ms |
| | Control relay: 220 V DC continuous current: 8 A breaking capacity: 0.3 A resistive |
| | making capacity: < 15 A for 200 ms Control relay: 24 V DC continuous current: 8 A breaking capacity: 4 A L/R < 40 ms |
| | making capacity: < 15 A for 200 ms Control relay: 24 V DC continuous current: 8 A breaking capacity: 6 A L/R < 20 ms |
| | making capacity: < 15 A for 200 ms |
| | Control relay: 24 V DC continuous current: 8 A breaking capacity: 8 A resistive making capacity: < 15 A for 200 ms |
| | Control relay: 48 V DC continuous current: 8 A breaking capacity: 1 A L/R < 40 ms making capacity: < 15 A for 200 ms |
| | Control relay: 48 V DC continuous current: 8 A breaking capacity: 2 A L/R < 20 ms |
| | making capacity: < 15 A for 200 ms Control relay: 48 V DC continuous current: 8 A breaking capacity: 4 A resistive |
| | making capacity: < 15 A for 200 ms |
| [Us] Rated Supply Voltage | 110/240 V AC 47.563 Hz tolerance: - 2010 % deactivated consumption: < 6 VA maximum consumption: < 15 VA 24/250 V DC tolerance: - 2010 % deactivated consumption: < 4.5 W maximum consumption: < 8 W |
| Supply Inrush Current | < 10 A for 10 ms at 24/250 V DC |
| | < 15 A at 110/240 V AC |
| Mounting Mode | Fixed |
| Mounting Support | Plate |
| Height | 222 mm |
| Width | 176 mm |
| Depth | 129 mm |
| Net Weight | 1.42 kg |
| Power Frequency Dielectric Withstand | 2 kV during 1 min conforming to IEC 60255-5 |
| [Uimp] Rated Impulse Withstand Voltage | 5 kV (1.2/50 μs) conforming to IEC 60255-5 |
| Mechanical Robustness | Earthquakes in operation (level: 2): 1 Gn (vertical axes) conforming to IEC 60255-21-3 Earthquakes in operation (level: 2): 2 Gn (horizontal axes) conforming to IEC 60255-21-3 Jolts de-energized (level: 2): 20 Gn/16 ms conforming to IEC 60255-21-2 Shocks de-energized (level: 2): 30 Gn/11 ms conforming to IEC 60255-21-2 Shocks in operation (level: 2): 10 Gn/11 ms conforming to IEC 60255-21-2 Vibrations de-energized (level: 2): 2 Gn, 10 Hz150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: 2): 1 Gn, 10 Hz150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: Pc): 2 Hz13.2 Hz, a = +/- 1 mm conforming to IEC 60068-2-6 |

Environment

| Standards | EN 50263 CSA C22.2 No 0.17-00 CSA C22.2 No 94-M91 CSA C22.2 No 14-95 UL 508 | |
|-------------------------------|---|--|
| Product Certifications | CE UL 508 file N° 212533 C22.2 file N° 210625 | |
| Fire Resistance | 650 °C conforming to IEC 60695-2-11 | |
| Ip Degree Of Protection | Other panels: IP20 conforming to IEC 60529 Front panel: IP52 conforming to IEC 60529 | |
| Nema Degree Of Protection | Type 12 conforming to NEMA | |
| Immunity To Microbreaks | 10 ms | |
| Electromagnetic Compatibility | 1 MHz damped oscillating wave: (immunity tests-conducted disturbances), III, 2.5 kV MC, 1 kV MD, conforming to IEC 60255-22-1 Fast transient bursts: (immunity tests-conducted disturbances), A or B, 4kV, 2.5 kHz/2 kV, 5 kHz, conforming to IEC 60255-22-4 Fast transient bursts: (immunity tests-conducted disturbances), IV, 4kV, 2.5 kHz, conforming to IEC 61000-4-4 Immunity to magnetic fields at network frequency: (immunity tests-radiated disturbances), IV, 30 A/m (continuous)-300 A/m (13 s), conforming to IEC 61000-4-8 Immunity to radiated fields: (immunity tests-radiated disturbances), III, 10 V/m, 80 MHz2 GHz, conforming to IEC 61000-4-3 Surges: (immunity tests-conducted disturbances), III, 2 kV MC, 1 kV MD, conforming to IEC 61000-4-5 1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV MC and MD, conforming to ANSI C37.90.1 100 kHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV MC, 1 kV MD, conforming to IEC 61000-4-12 Conducted disturbance emission: (emission tests), conforming to IEC 60255-25 Conducted disturbance emission: (emission tests), B, conforming to EN 55022 Disturbing field emission: (emission tests), A, conforming to EN 55022 Disturbing field emission: (emission tests), A, conforming to EN 55022 Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 4 kV contact, conforming to ANSI C37.90.3 Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 6 kV contact, conforming to IEC 60255-22-2 Fast transient bursts: (immunity tests-conducted disturbances), 10 V/m, 80 MHz 1 GHz, conforming to IEC 60255-22-6 Immunity to radiated fields: (immunity tests-radiated disturbances), 35 V/m, 25 MHz 1 GHz, conforming to ANSI C37.90.2 (1995) Voltage interruptions: (immunity tests-conducted disturbances), 30 W, 10 ms, conforming to IEC 60255-11 | |
| Climatic Withstand | Continuous exposure to damp heat (in operation): Ca: 10 days, 93 % RH, 40 °C (104 °F) conforming to IEC 60068-2-3 Continuous exposure to damp heat (in storage): Ca: 56 days, 93 % RH, 40 °C (104 °F) conforming to IEC 60068-2-3 Exposure to cold (in operation): Ab: - 25 °C (- 13 °F) conforming to IEC 60068-2-1 Exposure to cold (in storage): Ab: - 25 °C (- 13 °F) conforming to IEC 60068-2-1 Exposure to dry heat (in operation): Bb: 70 °C (158 °F) conforming to IEC 60068-2-2 Exposure to dry heat (in storage): Bb: 70 °C (158 °F) conforming to IEC 60068-2-2 Influence of corrosion/gaz test 2 (in operation): C: 21 days, 75 % RH, 25 °C (- 13 °F), 0.5 ppm H2S, 1 ppm S02 conforming to IEC 60068-2-60 Temperature variation with specified variation rate (in operation): Nb: - 25 °C to 70 °C (- 13 °F to 158 °F) 5 °C/min (41 °F/min) conforming to IEC 60068-2-14 Influence of corrosion/gaz test 4 (in operation): 21 days, 75 % RH, 25 °C, 0.01 ppm H2S, 0.2 ppm S02, 0.02 ppm NO2, 0.01 ppm Cl2 conforming to IEC 60068-2-60 Salt mist (in operation): Kb/2 conforming to IEC 60068-2-52 | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 12.200 cm |

| Package 1 Width | 27.200 cm |
|------------------------------|------------|
| Package 1 Length | 26.700 cm |
| Package 1 Weight | 1.206 kg |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 3 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 4.105 kg |
| Unit Type Of Package 3 | P12 |
| Number Of Units In Package 3 | 24 |
| Package 3 Height | 50.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 44.840 kg |



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |