Product datasheet

Specifications





impulse relay iTLs - 1P - 1NO -16A - coil 24 VDC - 48 VAC 50/60Hz

A9C32211

Main

| Range Of Product | Acti9 |
|-------------------------------|-----------------------------|
| Product Name | Acti9 iTL |
| Product Or Component Type | Impulse relay |
| Device Short Name | iTLs |
| Device Application | Remote indication |
| Poles | 1P |
| Pole Contact Composition | 1 NO |
| Auxiliary Contact Composition | 1 C/O |
| [In] Rated Current | 16 A |
| Network Type | AC |
| [Uc] Control Circuit Voltage | 48 V AC 50/60 Hz 24 V DC |

Complementary

| Network Frequency | 50/60 Hz |
|--------------------------------|---|
| [Ue] Rated Operational Voltage | 250 V AC 50/60 Hz |
| Control Type | Remote and manual control Coil deconnection |
| Control Signal Type | Impulse |
| Switching Frequency | 100 switching operations/day 5 switching operations/minute |
| Impulse Duration | 50 ms1 s |
| Remote Control Type | Illuminated push-button 3 mA |
| Local Signalling | ON/OFF indication |
| Signalling Circuit Voltage | AC: 24240 V DC: 24240 V |
| Signalling Output Current | 0.016 A |
| Mounting Mode | Fixed |
| Mounting Support | DIN rail |
| 9 Mm Pitches | 2 |
| Height | 84 mm |
| Width | 18 mm |
| Depth | 60 mm |

| Electrical Durability | AC-21: 200000 cycles AC-22: 100000 cycles | |
|-------------------------|---|--|
| Connections - Terminals | Control circuit: tunnel type terminals 1 cable(s) 0.54 mm² rigid Control circuit: tunnel type terminals 1 cable(s) 0.54 mm² rigid with cable end Control circuit: tunnel type terminals 1 cable(s) 14 mm² flexible Control circuit: tunnel type terminals 1 cable(s) 14 mm² flexible with ferrule Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² rigid Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² rigid with cable end Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² flexible Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² flexible with ferrule | |
| Wire Stripping Length | 11 mm | |
| Tightening Torque | 1 N.m | |
| Range Compatibility | Acti 9 iATEt Acti 9 iATLc Acti 9 iATLc+s Acti 9 iATLm Acti 9 iATLs Acti 9 iETL iTL 16 Acti 9 iATLc+c | |

Environment

| Standards | EN 669-2-2 EN 669-1 |
|---------------------------------------|---|
| Product Certifications | GOST CCC |
| Quality Labels | KEMA NF CEBEC IMQ VDE |
| Noise Level | 60 dB |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 (on opening) IP40 conforming to IEC 60529 (in enclosure) |
| Pollution Degree | 3 |
| Tropicalisation | 2 |
| Relative Humidity | 95 % at 55 °C |
| Ambient Air Temperature For Operation | -2050 °C |
| | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 7.500 cm |
| Package 1 Width | 2.000 cm |
| Package 1 Length | 8.500 cm |
| Package 1 Weight | 112.000 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 12 |
| Package 2 Height | 8.600 cm |
| Package 2 Width | 9.400 cm |
| Package 2 Length | 22.400 cm |

| Package 2 Weight | 1.399 kg |
|------------------------------|-----------|
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 144 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| Package 3 Weight | 17.466 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Mercury Free | |
|----------|------------------------------------|-----|
| ⊘ | Rohs Exemption Information | Yes |
| ⊘ | Halogen Free Plastic Parts Product | |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |