Product datasheet

Specification





iRTC relay- delays de-energizing a load upon opening- 1 O/C - Uc 24-240VAC/24VDC

A9E16067

- ! Discontinued on: Jan 23, 2021
- ! End-of-service on: Jan 24, 2021

Main

Relay Application	Time delay relay	
Time Delay Type	Delays de-energizing of a load upon contact opening	
Range	Acti9	
Product Name	IRT	
Device Short Name	IRTC	
Signal Contacts Composition	1 C/O	

Complementary

[le] Rated Operational Current	8 A at 250 V AC	
•	8 A at 250 V DC	
	0.01 A at 5 V DC	
	0.01 A at 3 v bc	
Impulse Duration	> 100 ms	
Local Signalling	LED, flashing for time delay	
Type Of Setting	Rotary knob: time delay configuration	
Time Delay Range	0.1360000 s	
Accuracy Error	+/- 10 %	
Repeat Accuracy	+/- 0.5 %	
[Uc] Control Circuit Voltage	24240 V AC 50/60 Hz	
[GG] Control Circuit Voltage	24 V DC	
	24 V DC	
[Us] Rated Supply Voltage	24240 V AC at 50/60 Hz	
2	24 V DC	
Mounting Mode	Fixed	
Mounting Support	35 mm symmetrical DIN rail	
9 Mm Pitches	2	
Height	93 mm	
Width	18 mm	
Depth	72 mm	
Net Weight	0.065 kg	
Colour	White	
Mechanical Durability	5000000 cycles	
Electrical Durability	AC-1: 100000 cycles	

Undervoltage Behaviour	100 ms
Connections - Terminals	Tunnel type terminals for 2 cable(s) 1.5 mm² flexible with cable end Tunnel type terminals for 2 cable(s) 1.5 mm² flexible without cable end Tunnel type terminals for 2 cable(s) 2.5 mm² rigid with cable end Tunnel type terminals for 2 cable(s) 2.5 mm² rigid without cable end

Environment

,	
Ip Degree Of Protection	IP20
Immunity To Microbreaks	20 ms
Ambient Air Temperature For Operation	-555 °C
Ambient Air Temperature For Storage	-4070 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2 cm
Package 1 Width	7.5 cm
Package 1 Length	10.2 cm
Package 1 Weight	79 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	40
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.621 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information