# **Product datasheet**

Specifications

#### Green Premium<sup>™</sup>



Miniature circuit breaker (MCB), Acti9 iC60a, 1P, 20A, C curve, 4500A (IEC/EN 60898-1), 6kA (IEC/EN 60947-2)

A9F64120

### Main

| Device Application        | Distribution   |
|---------------------------|--|
| Range                     | Acti9  |
| Product Name              | Acti9 iC60   |
| Product Or Component Type | Miniature circuit-breaker  |
| Device Short Name         | iC60a  |
| Poles Description         | 1P   |
| Number Of Protected Poles | 1  |
| [In] Rated Current        | 20 A   |
| Network Type              | AC   |
| Trip Unit Technology      | Thermal-magnetic   |
| Curve Code                | С  |
| Breaking Capacity         | 4500 A Icn at 230 V AC 50/60 Hz conforming to EN/IEC 60898-1<br>6 kA Icu at 220240 V AC 50/60 Hz conforming to EN/IEC 60947-2  |
| Utilisation Category      | Category A conforming to EN 60947-2<br>Category A conforming to IEC 60947-2  |
| Suitability For Isolation | Yes conforming to EN 60898-1<br>Yes conforming to EN 60947-2<br>Yes conforming to IEC 60898-1<br>Yes conforming to IEC 60947-2 |
| Standards                 | EN 60947-2<br>IEC 60898-1<br>IEC 60947-2<br>EN 60898-1   |

### Complementary

| Network Frequency                         | 50/60 Hz   |
|---|--|
| Magnetic Tripping Limit                   | 8 x ln +/- 20 %  |
| [Ics] Rated Service Breaking<br>Capacity  | 6 kA 100 % conforming to EN 60947-2 - 220240 V AC 50/60 Hz<br>6 kA 100 % conforming to IEC 60947-2 - 220240 V AC 50/60 Hz<br>4500 A 100 % conforming to EN 60898-1 - 230 V AC 50/60 Hz<br>4500 A 100 % conforming to IEC 60898-1 - 230 V AC 50/60 Hz |
| Limitation Class                          | 3 conforming to EN 60898-1<br>3 conforming to IEC 60898-1  |
| [Ui] Rated Insulation Voltage             | 500 V AC 50/60 Hz conforming to EN 60947-2<br>500 V AC 50/60 Hz conforming to IEC 60947-2  |
| [Uimp] Rated Impulse Withstand<br>Voltage | 6 kV conforming to EN 60947-2<br>6 kV conforming to IEC 60947-2  |
| Contact Position Indicator                | Yes  |

| Control Type             | Toggle  |
|--------------------------|---|
| Local Signalling         | Trip indicator  |
| Mounting Mode            | Removable comb busbar installed   |
| Mounting Support         | DIN rail  |
| 9 Mm Pitches             | 2   |
| Width                    | 18 mm   |
| Depth                    | 78.5 mm   |
| Colour                   | White   |
| Connections - Terminals  | Single terminal (top or bottom) 125 mm² rigid<br>Single terminal (top or bottom) 116 mm² flexible |
| Wire Stripping Length    | 14 mm for top or bottom connection  |
| Tightening Torque        | 2 N.m top or bottom   |
| Earth-Leakage Protection | Without   |

### Environment

| Ip Degree Of Protection                  | IP20 B conforming to EN/IEC 60529 |
|--|-----------------------------------|
| Pollution Degree                         | 3 conforming to EN 60947-2        |
|  | 3 conforming to IEC 60947-2       |
| Overvoltage Category                     | II                                |
| Tropicalisation                          | 2 conforming to EN/IEC 60068-2-78 |
| Relative Humidity                        | 95 %                              |
| Operating Altitude                       | 02000 m                           |
| Ambient Air Temperature For<br>Operation | -3570 °C                          |
| Ambient Air Temperature For<br>Storage   | -4085 °C                          |

## **Packing Units**

| -                            |          |
|------------------------------|----------|
| Unit Type Of Package 1       | PCE      |
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 7.3 cm   |
| Package 1 Width              | 1.7 cm   |
| Package 1 Length             | 9.4 cm   |
| Package 1 Weight             | 114 g    |
| Unit Type Of Package 2       | BB1      |
| Number Of Units In Package 2 | 12       |
| Package 2 Height             | 7.8 cm   |
| Package 2 Width              | 9.7 cm   |
| Package 2 Length             | 22.3 cm  |
| Package 2 Weight             | 1.412 kg |
| Unit Type Of Package 3       | S03      |
| Number Of Units In Package 3 | 132      |
| Package 3 Height             | 30 cm    |
| Package 3 Width              | 30 cm    |
|                              |          |

| Package 3 Length | 40 cm     |  |
|------------------|-----------|--|
| Package 3 Weight | 16.038 kg |  |
|                  |           |  |

### **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Halogen Free Product

### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information                       |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |