# **Product datasheet**

Specifications





# Control relay,Easy TeSys Control,CAE,2NO+2NC,<=690V, 48V AC 50Hz coil

CAE22E5

Discontinued on: May 19, 2023

① Discontinued

#### Main

Range	Easy TeSys
Range Of Product	Easy TeSys Control Relay
Product Or Component Type	Control relay
Device Short Name	CAE
Contactor Application	Control circuit
Colour	Grey (RAL 7011)

## Complementary

oomplemental y	
Utilisation Category	AC-14 AC-15
Pole Contact Composition	2 NO + 2 NC
[Ue] Rated Operational Voltage	<= 690 V AC
Control Circuit Type	AC at 50 Hz
[Uc] Control Circuit Voltage	48 V AC 50 Hz
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
[Ith] Conventional Free Air Thermal Current	10 A (at 40 °C)
Irms Rated Making Capacity	140 A at 690 V AC conforming to IEC 60947-5-1
[Icw] Rated Short-Time Withstand Current	120 A - 500 ms 140 A - 100 ms
Associated Fuse Rating	10 A gG at 690 V conforming to IEC 60947-5-1
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-5-1
Mounting Support	Plate Rail
Connections - Terminals	Screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Screw clamp terminals 1 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end
Recommended Tightening Torque	1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2
Control Circuit Voltage Limits	Operational: 0.851.1 Uc at 50 Hz Drop-out: 0.30.6 Uc
Operating Time	<ul> <li>419 ms coil energisation and NC opening</li> <li>1222 ms coil energisation and NO closing</li> <li>412 ms coil de-energisation and NC opening</li> <li>617 ms coil de-energisation and NO closing</li> </ul>

10 Mcycles
180 cyc/mn
70 VA 50 Hz (at 20 °C)
8 VA 50 Hz (at 20 °C)
17 V
5 mA
<ul><li>1.5 ms on energisation between NC and NO contact</li><li>1.5 ms on de-energisation between NC and NO contact</li></ul>
> 10 MOhm
Shocks control relay open: 7 Gn for 11 ms Shocks control relay closed: 10 Gn for 11 ms Vibrations control relay open: 1.5 Gn, 5300 Hz Vibrations control relay closed: 3 Gn, 5300 Hz
74 mm
45 mm
80 mm

#### Environment

Standards	IEC 60947-5-1
Product Certifications	GOST
Ip Degree Of Protection	IP2X conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068
Ambient Air Temperature For Operation	-2070 °C
Ambient Air Temperature For Storage	-6080 °C
Operating Altitude	3000 m without derating

#### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins