Product datasheet

Specifications

Full-Time Weatherproof Single Gang Socket Cover (Transparent) IP55

E223R_TR

Main

Product Or Component Type	Socket cover

Complementary

Wiring Device Mounting	Flush
Number Of Gangs	1 gang
Width	102.5 mm
Height	130.6 mm
Depth	50 mm

Environment

Environmental Characteristic	Weatherproof
Ip Degree Of Protection	IP55
Standards	GB 4208 GB 17466-1 IEC 60529

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6 cm
Package 1 Width	10.9 cm
Package 1 Length	13.8 cm
Package 1 Weight	163 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	30
Package 2 Height	19.2 cm
Package 2 Width	31 cm
Package 2 Length	49.9 cm
Package 2 Weight	5.484 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	240
Package 3 Height	80 cm
Package 3 Width	60 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 3 Length	105 cm
Package 3 Weight	48.87 kg

Contractual warranty

Warranty	18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency

RoHS/REACh

Well-being performance

Reach Free Of Svhc	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations