# **Product datasheet**

Specifications





# Contactor,Easy TeSys Control,LC1E,4P(4NO),AC-1 16A, 380V

LC1E06004Q7

Discontinued on: Jan 23, 2021

#### () Discontinued

#### Main

Range	Easy TeSys
Range Of Product	Easy TeSys Control
Product Or Component Type	Contactor
Device Short Name	LC1E
Contactor Application	Resistive load
Utilisation Category	AC-1
Poles Description	4P
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 50/60 Hz
[le] Rated Operational Current	16 A (at <60 °C) at <= 415 V AC AC-1 for power circuit
[Uc] Control Circuit Voltage	380 V AC 50/60 Hz

### Complementary

Pole Contact Composition	4 NO		
[Ith] Conventional Free Air Thermal Current	16 A (at 60 °C) for power circuit		
Irms Rated Making Capacity	60 A at 440 V AC for power circuit conforming to IEC 60947-4-1		
Rated Breaking Capacity	48 A at 440 V for power circuit conforming to IEC 60947		
[Icw] Rated Short-Time Withstand Current	<ul> <li>80 A 40 °C - 10 s for power circuit</li> <li>45 A 40 °C - 60 s for power circuit</li> <li>20 A 40 °C - 600 s for power circuit</li> </ul>		
Associated Fuse Rating	10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1 12 A gG at <= 690 V coordination type 1 for power circuit		
Average Impedance	2.5 mOhm - Ith 16 A 50 Hz for power circuit		
Power Dissipation Per Pole	0.09 W AC-3 1 W AC-1		
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-4-1		
Overvoltage Category	III		
Pollution Degree	3		
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947		
Mechanical Durability	1000000 cycles		
Electrical Durability	1400000 cycles AC-3 150000 cycles AC-1		
Control Circuit Type	AC at 50/60 Hz		

Control Circuit Voltage Limits	0.851.1 Uc (55 °C):operational 50/60 Hz 0.30.6 Uc (55 °C):drop-out 50/60 Hz		
Inrush Power In Va	95 VA 50 Hz cos phi 0.75 (at 20 °C) 95 VA 60 Hz cos phi 0.75 (at 20 °C)		
Hold-In Power Consumption In Va	Va 8.3 VA 50 Hz cos phi 0.3 (at 20 °C) 8.5 VA 60 Hz cos phi 0.3 (at 20 °C)		
Heat Dissipation	23 W for control circuit		
Operating Time	1222 ms on closing 419 ms on opening		
Maximum Operating Rate	1800 cyc/h 60 °C		
Connections - Terminals	Power circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.6 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.6 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.6 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 12.6 mm <sup>2</sup> - cable stiffness: solid without cable end		
Tightening Torque	Power circuit: 1.2 N.m Control circuit: 1.2 N.m		
Minimum Switching Voltage	17 V for control circuit		
Minimum Switching Current	5 mA for control circuit		
Insulation Resistance	> 10 MOhm for control circuit		
Non-Overlap Time	<ol> <li>1.5 ms on energisation guaranteed between NC and NO contact</li> <li>1.5 ms on de-energisation guaranteed between NC and NO contact</li> </ol>		
Mounting Support	DIN rail Plate		

## Environment

Standards	IEC 60947-1
Product Certifications	CE EAC
Ip Degree Of Protection	IP2X conforming to IEC 60529
Protective Treatment	TH (pollution degree 3) conforming to IEC 60068-2-30
Permissible Ambient Air Temperature Around The Device	-2070 °C at Uc -6080 °C storage -555 °C operation
Operating Altitude	3000 m without derating
Fire Resistance	850 °C conforming to IEC 60695-2-1
Mechanical Robustness	Vibrations contactor open (1.5 Gn, 5300 Hz) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor open (7 Gn for 11 ms) Shocks contactor closed (10 Gn for 11 ms)
Height	74 mm
Width	45 mm

Depth	80 mm	
Net Weight	0.34 kg	
Packing Units		
Unit Type Of Package 1	PCE	

Number Of Units In Package 1

1

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc
 Toxic Heavy Metal Free
 Mercury Free
 Rohs Exemption Information Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins