Product datasheet

Specification





differential thermal overload relay, TeSys K, 0.8...1.2A, class 10A

LR2K0306

Main

Range	TeSys
Product Name	TeSys LRK
Product Or Component Type	Differential thermal overload relay
Device Short Name	LR2K
Relay Application	Motor protection
Product Compatibility	LC1K LC7K LP4K LP1K
Network Type	AC DC
Thermal Overload Class	Class 10A conforming to IEC 60947-4-1
Thermal Protection Adjustment Range	0.81.2 A
[Ui] Rated Insulation Voltage	Power circuit: 690 V conforming to BS 4941 Power circuit: 690 V conforming to IEC 60947 Power circuit: 750 V conforming to VDE 0110 group C Power circuit: 600 V conforming to CSA C22.2 No 14

Complementary

Network Frequency	<= 400 Hz
Mounting Support	Under contactor
	Plate, with specific accessories
	Rail, with specific accessories
	Tail, mai oposiio accessios
Auxiliary Contact Composition	1 NO + 1 NC
[Ith] Conventional Free Air	6 A for signalling circuit
Thermal Current	
[Ue] Rated Operational Voltage	<= 690 V for power circuit
	690 V AC AC-15 for signalling circuit
	250 V DC DC-13 for signalling circuit
	230 V DC DC-13 for signalling circuit
Associated Fuse Rating	6 A gG for signalling circuit conforming to VDE 0660
	6 A gG for signalling circuit conforming to VBE 3000
	0 A go for signaling circuit comorning to 120 00947
[Uimp] Rated Impulse Withstand	6 kV
Voltage	
Power Dissinction Bor Bala	OW
Power Dissipation Per Pole	2 W
Phase Failure Sensitivity	Voc conferming to IFO 60047.4.4
Friase Failure Sensitivity	Yes conforming to IEC 60947-4-1
Local Signalling	Trip indicator (yellow)
Loodi oigilalilig	The indicator (yellow)
Control Type	Red push-button: trip test function
	Blue push-button: stop and manual reset
	· · · · · · · · · · · · · · · · · · ·
	selector switch: manual or automatic reset

Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end
1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm 1.3 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
58 mm
45 mm
65 mm
0.145 kg

Environment

Standards	NF C 63-650 IEC 60947
	BS 4941
	VDE 0660
	VDE 0000
Product Certifications	UL
	CSA
	UKCA
Protective Treatment	TC conforming to IEC 60068
	TC conforming to DIN 50016
Ip Degree Of Protection	IP2X conforming to IEC 60529
	1F2X comorning to the 60029
Ambient Air Temperature For	-2055 °C without derating conforming to IEC 60947
Operation	-3060 °C with derating conforming to IEC 60947
Ambient Air Temperature For	-4070 °C
Storage	
Operating Altitude	2000 m without derating
	
Fire Resistance	850 °C conforming to IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
	Requirement 2 conforming to NF F 16-101
	Requirement 2 conforming to NF F 16-102
	Requirement 2 conforming to NF F 16-102
Mechanical Robustness	Shocks NO contact: 10 Gn for 11 ms conforming to IEC 60068-2-27
	Shocks NC contact: 10 Gn for 11 ms conforming to IEC 60068-2-27
	Vibrations NO contact: 2 Gn, 5300 Hz conforming to IEC 60068-2-6
	Vibrations NC contact: 2 Gn, 5300 Hz conforming to IEC 60068-2-6
	VIDIALIONS INC CONTACT. 2 GH, 5300 HZ CONTOTHING TO IEC 00000-2-0

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.200 cm
Package 1 Width	4.800 cm
Package 1 Length	8.500 cm
Package 1 Weight	155.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	41
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm

Package 2 Weight

6.775 kg

Contractual warranty

Warranty

Apr 23, 2024

18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information