Product datasheet

Specifications





ClimaSys standard cooling unit side of enclosure - 820W at 230 V

NSYCU800

Overview

Lead Time

Usually Ships within 4 Weeks

Main

Mann	
Range	ClimaSys
Product Name	CU
Product Or Component Type	Cooling unit
Mounting Type	Side
Installation	Indoor side
Product Destination	For enclosure
Mounting Mode	By screws
Supply Voltage	230 V AC at 50/60 Hz, 1 phase
Rated Power	820 W
Cooling Power	820 W 50/60 Hz L35-L35 680 W 50/60 Hz L35-L50

Complementary

Height	783 mm
Width	348 mm
Depth	215 mm
[In] Rated Current	2.6 A
Inrush Current	10.8 A
Power Consumption In W	440 W at 50/60 Hz, L35-L35 490 W at 50/60 Hz, L35-L50
Energy Efficiency Ratio	1.9
Control Type	Electronic controller
Temperature Setting Range	2055 °C at 50 Hz 2050 °C at 60 Hz
Ambient Air Temperature For Operation	2046 °C inside the enclosure: 55 °C maximum: 2055 °C at 50 Hz outside the enclosure: 2050 °C at 60 Hz outside the enclosure:
Noise Level	65 dB conforming to EN/ISO 3746
Pressure	25 bar
Flow Rate	Internal circuit: 330 m3/h at 50/60 Hz External circuit: 570 m3/h at 50/60 Hz

Net Weight	27 kg	
Cooling Gas Type	R134a (0.23 kg)	
Type Of Filter	Optional external circuit filter	
Protection Type	Thermal protection: T 6 A Short-circuit protection (magnetic):	
Material	Steel	
Colour	Grey (RAL 7035)	

Environment

Product Certifications	CE
Directives	2006/42/EC - machinery 2006/95/EC - low voltage directive 2004/108/EC - electromagnetic compatibility
Standards	EN 60204-1 EN/ISO 12100 EN 60335-2-40 EN 378 EN 60335-1
Ip Degree Of Protection	IP54 conforming to IEC 60529 (on the internal circuit) IP34 conforming to IEC 60529 (on the external circuit)

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	21.5 cm
Package 1 Width	34.8 cm
Package 1 Length	78.3 cm
Package 1 Weight	27.0 kg
Unit Type Of Package 2	P12
Number Of Units In Package 2	6
Package 2 Height	103.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	212.0 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information