Product datasheet

Specifications





Terminal block, Linergy TR, greenyellow, 2.5mm2, 2 level connt, protective earth, 4 points, Set of 50

NSYTRV24DPE

Discontinued on: Nov 1, 2020

(!) Discontinued

Main

Range	Linergy	
Product Name	Linergy TR	
Product Or Component Type	Terminal block	
Device Short Name	TRV	
Terminal Block Type	Protective earth	
Terminal Block Level	2	
Mounting Mode	Clip-on	
Nominal Cross Section	2.5 mm²	
Length	69.9 mm	
Colour	Green-yellow	
Quantity Per Set	Set of 50	

Complementary

Joinplomontal y		
Width	5.2 mm	
Height	65 mm	
Connections - Terminals	1 x screw terminal: upstream 1 x screw terminal: downstream	
Number Of Connections	2	
Connection Position	Sideways	
Number Of Measurement Input 4		
Cable Cross Section	0.144 mm², solid 0.22.5 mm², flexible with cable end 0.144 mm², flexible without cable end	
Tightening Torque	0.50.6 N.m	
Wire Stripping Length	9 mm	
Tool Type	Connection: screwdriver Disconnection: screwdriver	
Material	Polyamide 6/6: insulating case	
Dielectric Loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4	
Dielectric Constant	3.7 at 1 MHz	
Resistivity	10000 M Ω .m conforming to IEC 60093 10000 M Ω .m conforming to VDE 0303-T30	

Surface Resistance	1000 G Ω conforming to IEC 60093 1000 G Ω conforming to VDE 0303-T30	
Creep Resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30	
Flame Retardance	V0, thickness0.8 mm conforming to UL 94	
Net Weight	21 g	
Range Compatibility	Prisma G Prisma P Prisma PH Prisma Pack Spacial Kaedra Pragma TeSys	
Product Compatibility	Spacial enclosures	

Environment

Product Certifications	ATEX	
	CSA	
	DNV	
	EAC	
	LR	
	IEC-Ex	
	cURus	
	GL	
Dielectric Strength	1000 V conforming to IEC 60243-1	
Ambient Air Temperature For Operation	-40130 °C conforming to IEC 60216-1 -40130 °C conforming to VDE 0304-T21	

Packing Units

Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	6.900 cm	
Package 1 Width	8.000 cm	
Package 1 Length	27.000 cm	
Package 1 Weight	20.000 g	
Unit Type Of Package 2	BB1	
Number Of Units In Package 2	50	
Package 2 Height	6.900 cm	
Package 2 Width	8.000 cm	
Package 2 Length	27.000 cm	
Package 2 Weight	1.024 kg	
Unit Type Of Package 3	S03	
Number Of Units In Package 3	500	
Package 3 Height	30.000 cm	
Package 3 Width	30.000 cm	
Package 3 Length	40.000 cm	
Package 3 Weight	10.668 kg	

Contractual warranty

Warranty

May 4, 2024

18 months

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations

May 4, 2024