# **Product datasheet**





Pre assembled and pre cabled beacon, Harmony XVM, without buzzer + 1 illuminated unit, Ø 45 mm, 24 V AC/DC

XVMB2RWSB



(!) Discontinued on: Sep 21, 2021

# Main

Range Of Product	Harmony XVM
Product Or Component Type	Pre-assembled and pre-cabled beacon
Beacon Or Indicator Bank Unit Type	1 illuminated unit
Component Name	XVM
Light Source	Red super bright LED with BA 15d base steady signalling
Light Block Color	Red
[Us] Rated Supply Voltage	24 V AC/DC
Indicator Bank Base Type	Base without buzzer
Mounting Mode	Horizontal

# Complementary

Kit Composition	Cover Plastic fixing plate Base unit		
Mounting Diameter	45 mm		
Connections - Terminals	Flying leads,clamping capacity: 1 x 0.325 mm² (AWG 22)		
Marking	CE		
Mounting Support	base		
Short-Circuit Protection	0.2 A		
[Ui] Rated Insulation Voltage	250 V conforming to IEC 60947-1		
Nominal Voltage Limit	0.851.1 Un conforming to IEC 60947-5-1		
Current Consumption	18 mA on base unit 20 mA on flash discharge tube unit		
[Uimp] Rated Impulse Withstand Voltage	4 kV conforming to IEC 60947-1		
Flashing Frequency	0.8 Hz		
Fundamental Frequency	4 kHz		
Net Weight	0.143 kg		

#### **Environment**

Ip Degree Of Protection	IP54 horizontal position conforming to IEC 60529	
Product Certifications	CCC	

Life Is On Schneider Apr 20, 2024

Standards	EN/IEC 60947-1	
	EN/IEC 60947-5-1	
Ambient Air Temperature For Storage	-2570 °C	
Ambient Air Temperature For Operation	-1050 °C	
Overvoltage Category	Class II conforming to IEC 60947-1	
	Class II conforming to IEC 60947-5-1	
	Class II conforming to IEC 61140	
Protective Treatment	тс	
Noise Level	080 dB at 1 m	

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration		
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)		
China Rohs Regulation	China RoHS declaration		
<b>Environmental Disclosure</b>	Product Environmental Profile		
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		
Circularity Profile	No need of specific recycling operations		


#### XVMB2RWSB

#### **Dimensions Drawings**

Pre-Assembled and Pre-Cabled Tower Light with Fixing Base for Mounting on Horizontal Support (Plastic Fixing Plate)

#### **Dimensions**

Below drawing shows a tower light with 3 illuminated stages. Select the number of stages according to the product characteristics in order to get **b** dimension.



#### (1) Base unit with or without buzzer.

Number of illuminated units	b in mm	b in in.
1 unit	150	5.90
2 units	215	8.46
3 units	280	11.02
4 units	345	13.58

# **Product datasheet**

## XVMB2RWSB

#### Connections and Schema

#### **Pre-Assembled and Pre-Cabled Tower Light**

#### **Wire Colors**

4th illuminated unit: yellow wire 3rd illuminated unit: green wire 2nd illuminated unit: white wire 1st illuminated unit: blue wire

Common: black wire

Apr 20, 2024

Buzzer (if integrated in base unit): grey wire