Product data sheet

Specifications

FR.PL.HZ.FIX.NS1600TOG/ROT.4P

03687

⚠ **Discontinued on:** Apr 25, 2023

⚠ **Discontinued**

Main

Range	Prisma
Range Of Product	Prisma P
Product Or Component Type	Front plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma P cubicle
Type Of Front Plate	Cut-out
Installed Device	ComPact: fixed NS630b...1000 - control: toggle - horizontal installation ComPact: fixed NS630b...1000 - control: direct front rotary handle - horizontal installation
Poles Description	1 x 3P: mounting plate support: NS630b...1000 horizontal installation 1 x 4P: mounting plate support: NS630b...1000 horizontal installation
Operating Position	Horizontal

Complementary

Enclosure/Cubicle Description	Cubicle - width 650 mm depth 800 mm Cubicle + duct - width 650 mm depth 400 mm
Connection Position	Front connection Rear connection
Number Of Vertical Modules [50 Mm]	7
Standards	IEC 61439-1 IEC 61439-2
Product Certifications	ASEFA
Material	Steel
Surface Finish	Matt Smooth
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)
Height	350 mm
Width	500 mm
Net Weight	1.78 kg
Quantity Per Set	Set of 1

Functional Unit	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed toggle horizontal 3P 1 front connection 7
	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed toggle horizontal 3P 1 connection transfer assembly 8
	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed direct front rotary handle horizontal 3P 1 front connection 7
	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed direct front rotary handle horizontal 3P 1 connection transfer assembly 8
	650 mm 800 mm Prisma P cubicle ComPact NS630b...1000 fixed toggle horizontal 3P 1 rear connection 7
	650 mm 800 mm Prisma P cubicle ComPact NS630b...1000 fixed direct front rotary handle horizontal 3P 1 rear connection 7
	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed toggle horizontal 4P 1 front connection 7
	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed toggle horizontal 4P 1 connection transfer assembly 8
	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed direct front rotary handle horizontal 4P 1 front connection 7
	650 mm 400 mm Prisma P cubicle + duct ComPact NS630b...1000 fixed direct front rotary handle horizontal 4P 1 connection transfer assembly 8
	650 mm 800 mm Prisma P cubicle ComPact NS630b...1000 fixed toggle horizontal 4P 1 rear connection 7
	650 mm 800 mm Prisma P cubicle ComPact NS630b...1000 fixed direct front rotary handle horizontal 4P 1 rear connection 7

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.6 cm
Package 1 Width	35 cm
Package 1 Length	50 cm
Package 1 Weight	1.795 kg
Unit Type Of Package 2	CAR
Number Of Units In Package 2	5
Package 2 Height	37 cm
Package 2 Width	31 cm
Package 2 Length	52 cm
Package 2 Weight	8.975 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	20
Package 3 Height	73 cm
Package 3 Width	80 cm
Package 3 Length	60 cm
Package 3 Weight	35.9 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Transparency   RoHS/REACh

Well-being performance

✅ Reach Free Of Svhc

✅ Toxic Heavy Metal Free

✅ Mercury Free

✅ Rohs Exemption Information   Yes

Certifications & Standards

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

EU RoHS Declaration

China Rohs Regulation   China RoHS declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure   Product Environmental Profile

Circularity Profile   End of Life Information