


# Product data sheet

Specifications



## PLAIN FRONT PLATE WIDTH 600/650 4M

03804

 **Discontinued on:** Apr 25, 2023

 **Discontinued**

### Main

|                                    |  |
|------------------------------------|--|
| Range                              | Prisma   |
| Range Of Product                   | Prisma G<br>Prisma P   |
| Product Or Component Type          | Front plate  |
| Accessory / Separate Part Category | Installation accessory   |
| Range Compatibility                | Prisma Prisma G enclosure<br>Prisma Prisma P cubicle   |
| Type Of Front Plate                | Plain  |
| Installed Device                   | TeSys: fixed TeSys U - horizontal installation<br>Altistart: ATS01N103/106FT<br>Phaseo: LV/LV transformer<br>Enerlin'X: FDM128 |
| Poles Description                  | 9 x 3P: modular rail support: TeSys U horizontal installation  |

### Complementary

|                                    |  |
|------------------------------------|--|
| Enclosure/Cubicle Description      | Floor-standing enclosure - width 600 mm<br>Wall-mounted enclosure - width 600 mm<br>Cubicle - width 650 mm depth 400 mm<br>Pack enclosure - width 555 mm |
| Number Of Vertical Modules [50 Mm] | 4  |
| Standards                          | IEC 61439-1<br>IEC 61439-2   |
| Product Certifications             | ASEFA  |
| Material                           | Steel  |
| Surface Finish                     | Matt<br>Smooth   |
| Protective Treatment               | Electrophoresis treatment and hot-polymerised polyester epoxy powder   |
| Colour                             | White (RAL 9001)   |
| Height                             | 200 mm   |
| Width                              | 500 mm   |
| Net Weight                         | 0.86 kg  |
| Quantity Per Set                   | Set of 1   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                 |   |
|-----------------|---|
| Functional Unit | 600 mm Prisma G floor-standing enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4 |
|                 | 600 mm Prisma G wall-mounted enclosure TeSys TeSys U fixed horizontal 3P 9 direct 4   |
|                 | 650 mm 400 mm Prisma P cubicle TeSys TeSys U fixed horizontal 3P 9 direct 4           |
|                 | 600 mm Prisma G floor-standing enclosure Altistart ATS01N103/106FT 19 4               |
|                 | 600 mm Prisma G wall-mounted enclosure Altistart ATS01N103/106FT 19 4                 |
|                 | 650 mm 400 mm Prisma P cubicle Altistart ATS01N103/106FT 19 4                         |
|                 | 600 mm Prisma G floor-standing enclosure Phaseo LV/LV transformer 4                   |
|                 | 600 mm Prisma G wall-mounted enclosure Phaseo LV/LV transformer 4                     |
|                 | 650 mm 400 mm Prisma P cubicle Phaseo LV/LV transformer 4                             |
|                 | 650 mm 400 mm Prisma P cubicle Enerlin'X FDM128 4 4                                   |

## Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type Of Package 1       | PCE        |
| Number Of Units In Package 1 | 1          |
| Package 1 Height             | 3.000 cm   |
| Package 1 Width              | 20.000 cm  |
| Package 1 Length             | 50.000 cm  |
| Package 1 Weight             | 828.000 g  |
| Unit Type Of Package 2       | CAR        |
| Number Of Units In Package 2 | 10         |
| Package 2 Height             | 16.800 cm  |
| Package 2 Width              | 22.500 cm  |
| Package 2 Length             | 52.500 cm  |
| Package 2 Weight             | 8.480 kg   |
| Unit Type Of Package 3       | P12        |
| Number Of Units In Package 3 | 360        |
| Package 3 Height             | 104.000 cm |
| Package 3 Width              | 80.000 cm  |
| Package 3 Length             | 120.000 cm |
| Package 3 Weight             | 317.280 kg |

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

✓ Halogen Free Plastic Parts Product

## Certifications & Standards

|                          |   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>           |
| China Rohs Regulation    | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>   |