

mini Kaedra - for modular device - 1 openings - 6 modules - 1 terminal block

13958

! Discontinued on: Dec 31, 2023

(!) Discontinued

Main

| Range | Kaedra |
|-------------------------------------|---|
| Product Or Component Type | Weatherproof enclosure |
| Enclosure Type | Mini enclosure for modular device |
| Accessories Included With Enclosure | 1 marking kit 1 terminal block 8 holes 1 terminal block support |
| Mounting Plate Description | Slotted |

Complementary

| Enclosure Mounting | Surface |
|------------------------------------|---|
| 9 Mm Pitches | 12 |
| Number Of 18 Mm Modules Per Row | 6 |
| Total Number Of 18 Mm Modules | 6 |
| Number Of Horizontal Rows | 1 |
| Electrical Insulation Class | Class II Double insulation |
| Provided Equipment | 1 marking kit 1 terminal block 8 holes 1 terminal block support |
| Type Of Front Cover | Transparent |
| Power Dissipation In W | 11 W |
| [In] Rated Current | 63 A |
| Type Of Rail | DIN |
| Number Of Pre-Cutouts Pg Iso | 3 |
| Number Of Terminal Blocks | 1 with 8 outgoers |
| Distribution Block Outgoers | 4 x 10 mm ² 4 x 16 mm ² |
| Locking Options Description | Optional keylock |
| Enclosure Material | Self-extinguishing polymer |
| Width | 159 mm |
| Height | 200 mm |
| Depth | 112 mm |
| Internal Depth | 56 mm |

Colour Door: transparent green
Enclosure: light grey (RAL 7035)

Environment

| Standards | IEC 60439-3 EN 50102 IEC 60529 IEC 670 EN 50262 |
|---------------------------------------|--|
| Fire Resistance | 750 °C conforming to IEC 60695-2-1 |
| Ip Degree Of Protection | IP65 conforming to IEC 60529 |
| Ik Degree Of Protection | IK09 conforming to EN 50102 |
| Environmental Characteristics (Uv) | UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013 |
| Overvoltage Category | II |
| Ambient Air Temperature For Operation | -2560 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 11.150 cm |
| Package 1 Width | 16.000 cm |
| Package 1 Length | 20.000 cm |
| Package 1 Weight | 586.000 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 7 |
| Package 2 Height | 22.000 cm |
| Package 2 Width | 34.500 cm |
| Package 2 Length | 40.500 cm |
| Package 2 Weight | 4.374 kg |
| Unit Type Of Package 3 | P12 |
| Number Of Units In Package 3 | 168 |
| Package 3 Height | 80.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 119.880 kg |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Mercury Free | |
|-----------------------------|---|
| Pulse Formation Information | |
| Rohs Exemption Information | Yes |
| | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| | Product out of China RoHS scope. Substance declaration for your information |