


# Product data sheet

Specifications



## circuit breaker Compact NS160H - TMD - 125 A - 1 pole 1d

30590

❗ Discontinued

### Main

|                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range Of Product                       | Compact NS100...630                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Product Or Component Type              | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Device Short Name                      | Compact NS160H                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Circuit Breaker Name                   | Compact NS160H                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Device Application                     | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Poles Description                      | 1P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Protected Poles Description            | 1t                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Network Type                           | DC<br>AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Network Frequency                      | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| [In] Rated Current                     | 150 A at 65 °C<br>160 A at 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| [Ui] Rated Insulation Voltage          | 750 V AC 50/60 Hz conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| [Ue] Rated Operational Voltage         | 690 V AC 50/60 Hz conforming to IEC 60947-2<br>750 V DC conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Breaking Capacity Code                 | H                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Breaking Capacity                      | 100 kA at 240 V AC 50/60 Hz conforming to NEMA AB1 HIC<br>35 kA at 600 V AC 50/60 Hz conforming to NEMA AB1 HIC<br>65 kA at 480 V AC 50/60 Hz conforming to NEMA AB1 HIC<br>10 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 600 V AC 50/60 Hz conforming to UL 508<br>85 kA at 240 V AC 50/60 Hz conforming to UL 508<br>65 kA at 480 V AC 50/60 Hz conforming to UL 508<br>100 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] Rated Service Breaking Capacity  | 10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>50 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>70 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 600 V AC 50/60 Hz conforming to UL 508<br>85 kA at 240 V AC 50/60 Hz conforming to UL 508<br>100 kA at 240 V AC 50/60 Hz conforming to NEMA AB1 HIC<br>35 kA at 600 V AC 50/60 Hz conforming to NEMA AB1 HIC<br>65 kA at 480 V AC 50/60 Hz conforming to NEMA AB1 HIC<br>65 kA at 480 V AC 50/60 Hz conforming to UL 508                         |
| Suitability For Isolation              | Yes conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                      |                                                                      |
|----------------------|----------------------------------------------------------------------|
| Utilisation Category | Category A                                                           |
| Trip Unit Name       | TM-D                                                                 |
| Trip Unit Technology | Thermal-magnetic                                                     |
| Trip Unit Rating     | 125 A                                                                |
| Protection Type      | Overload protection (thermal)<br>Short-circuit protection (magnetic) |
| Pollution Degree     | 3 conforming to IEC 60947                                            |

## Complementary

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Control Type                             | Toggle                                                                                                                       |
| Mounting Mode                            | Fixed                                                                                                                        |
| Mounting Support                         | Backplate                                                                                                                    |
| Upside Connection                        | Front                                                                                                                        |
| Downside Connection                      | Front                                                                                                                        |
| Mechanical Durability                    | 20000 cycles                                                                                                                 |
| Electrical Durability                    | 10000 cycles 277 V AC 50/60 Hz In conforming to IEC 60947-2<br>20000 cycles 277 V AC 50/60 Hz In/2 conforming to IEC 60947-2 |
| Connection Pitch                         | 35 mm                                                                                                                        |
| Local Signalling                         | Positive contact indication                                                                                                  |
| Long Time Pick-Up Adjustment Type Ir     | Fixed                                                                                                                        |
| Long Time Pick-Up Adjustment Range       | 0.8...1 x In                                                                                                                 |
| Long Time Delay Adjustment Type          | Fixed                                                                                                                        |
| Instantaneous Pick-Up Adjustment Type Ii | Fixed                                                                                                                        |
| Instantaneous Pick-Up Adjustment Range   | 1250 A                                                                                                                       |
| Height                                   | 161 mm                                                                                                                       |
| Width                                    | 105 mm                                                                                                                       |
| Depth                                    | 86 mm                                                                                                                        |

## Environment

|                                       |                               |
|---------------------------------------|-------------------------------|
| Standards                             | IEC 60947-2                   |
| Product Certifications                | KEMA<br>ASTA<br>LCIE<br>ASEFA |
| Ip Degree Of Protection               | IP40 conforming to IEC 60529  |
| Ik Degree Of Protection               | IK07 conforming to EN 50102   |
| Ambient Air Temperature For Operation | -25...70 °C                   |
| Ambient Air Temperature For Storage   | -50...85 °C                   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|