

low level auxiliary contact, ComPact NS630b to NS1600, drawout, circuit breaker status OF, 1 changeover contact type

33804

Main

Product Or Component Type	Auxiliary contact
Device Short Name	OF
Device Application	Breaker status monitoring
Range Compatibility	ComPact ComPact NS630b1600
Signal Contacts Composition	1 NO/NC

Complementary

· · · · · · · · · · · · · · · · · ·	
Local Signalling	ON/OFF indication for open/close
Auxiliary Contacts Type	Low level
Mounting Mode	Clip-on
[Ith] Conventional Free Air Thermal Current	5 A
Breaking Capacity (A)	AC-12: 5 A at 24 V AC 50/60 Hz
	AC-12: 5 A at 48 V AC 50/60 Hz
	AC-12: 5 A at 110 V AC 50/60 Hz
	AC-12: 5 A at 220/240 V AC 50/60 Hz
	AC-12: 5 A at 380/440 V AC 50/60 Hz
	AC-12: 5 A at 480 V AC 50/60 Hz
	AC-15: 3 A at 24 V AC 50/60 Hz
	AC-15: 3 A at 48 V AC 50/60 Hz
	AC-15: 2.5 A at 110 V AC 50/60 Hz
	AC-15: 2 A at 220/240 V AC 50/60 Hz
	AC-15: 1.5 A at 380/440 V AC 50/60 Hz
	AC-15: 1 A at 480 V AC 50/60 Hz
	DC-12: 5 A at 24 V DC 50/60 Hz
	DC-12: 2.5 A at 48 V DC 50/60 Hz
	DC-12: 0.6 A at 110 V DC
	DC-12: 0.3 A at 250 V DC
	DC-14: 1 A at 24 V DC
	DC-14: 0.2 A at 48 V DC
	DC-14: 0.05 A at 110 V DC
	DC-14: 0.03 A at 250 V DC
Minimum Load	1 mA at 4 V DC
Accessory / Separate Part Category	Spare part for Compact NS630b1600

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	5.0 cm
Package 1 Length	15.0 cm
Package 1 Weight	88.0 q

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Eu Rohs Directive	Compliant EU RoHS Declaration
Reach Regulation	REACh Declaration
✓ Pvc Free	
Rohs Exemption Information	Yes
Mercury Free	
Toxic Heavy Metal Free	
Reach Free Of Svhc	