# Product data sheet

Specifications

Thorsman - INKA-IH101 - internal corner - 72 mm - natural

5504100

⚠ **Discontinued on:** Jun 30, 2023

⚠ **Discontinued**

Main

Range Of Product	Thorsman
Product Name	Thorsman INKA
Product Or Component Type	Internal corner
Colour Tint	Natural
Quantity Per Set	Set of 1

Complementary

Trunking Material	Aluminium
Trunking Dimension	101 x 72 mm
Material	Aluminium anodized
Length	200 mm
Height	100 mm
Width	200 mm

Environment

Directives	93/68/EEC - low voltage directive
Standards	EN 50085-1
Ambient Air Temperature For Operation	-20…60 °C
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	17.0 cm
Package 1 Width	21.5 cm
Package 1 Length	23.0 cm
Package 1 Weight	495.0 g
Unit Type Of Package 2	PAL
Number Of Units In Package 2	99
Package 2 Height	95.0 cm
Package 2 Width	80.0 cm

Package 2 Length	120.0 cm
Package 2 Weight	92.231 kg

Contractual warranty

Warranty	18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium 〉

Guide to assess a product's sustainability 〉

Transparency   RoHS/REACh

Well-being performance

✔ Reach Free Of Svhc

✔ Toxic Heavy Metal Free

✔ Mercury Free

✔ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation   REACh Declaration

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

EU RoHS Declaration

China Rohs Regulation   China RoHS declaration

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure   Product Environmental Profile

Circularity Profile   No need of specific recycling operations