# Product data sheet

Specifications

Pilot light, Harmony 9001K, metal, polycarbonate, fresnel lens, red, 30mm, 110...120V

9001KP1R31

## Main

| | |
|---|---|
| Range Of Product | Harmony 9001K |
| Product Or Component Type | Pilot light |
| Device Short Name | K |

## Complementary

| | |
|---|---|
| Bezel Material | Metal |
| Mounting Diameter | 30 mm |
| Lens Type | Fresnel plastic |
| Cap/Operator Or Lens Colour | Red |
| Light Source | incandescent |
| Bulb Base | BA 9s |
| Light Block Supply | Via transformer 120 V AC 50/60 Hz<br>Via integral transformer 110 V AC 50/60 Hz |
| Connections - Terminals | Screw clamp terminals, 1 x 0.22...2 x 1.5 mm² conforming to IEC 60947-1 |
| Shape Of Screw Head | Round |
| Operating Position | Any position |
| Light Source | Incandescent bulb |
| [Us] Rated Supply Voltage | 110...120 V AC |
| Operating Mode | Normal |
| Device Presentation | Complete product |
| Lens Type | Fresnel |
| [Us] Rated Supply Voltage | 110...120 V |
| Light Block Supply | Via integral transformer |
| Supply Frequency | 50...60 Hz |
| Lens Material | Polycarbonate |
| Size | 30 mm |

## Environment

| | |
|---|---|
| Product Certifications | UL listed file E42259 CCN NKCR<br>CSA LR25490 class 3211 03<br>CE |
| Nema Degree Of Protection | NEMA 1/2/3/3R/4/6/12/13 |

# Packing Units

| | |
|---|---|
| **Unit Type Of Package 1** | PCE |
| **Number Of Units In Package 1** | 1 |
| **Package 1 Height** | 4.826 cm |
| **Package 1 Width** | 5.588 cm |
| **Package 1 Length** | 9.144 cm |
| **Package 1 Weight** | 222.300 g |
| **Unit Type Of Package 2** | S01 |
| **Number Of Units In Package 2** | 16 |
| **Package 2 Height** | 15 cm |
| **Package 2 Width** | 15 cm |
| **Package 2 Length** | 40 cm |
| **Package 2 Weight** | 3.757 kg |
| **Unit Type Of Package 3** | P06 |
| **Number Of Units In Package 3** | 512 |
| **Package 3 Height** | 75.000 cm |
| **Package 3 Width** | 80.000 cm |
| **Package 3 Length** | 60.000 cm |
| **Package 3 Weight** | 128.218 kg |

Life Is On | Schneider Electric

# Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ⟩

Guide to assess a product's sustainability ⟩

Transparency    RoHS/REACh

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information          Yes

## Certifications & Standards

| | |
|---|---|
| **Reach Regulation** | REACh Declaration |
| **Eu Rohs Directive** | Pro-active compliance (Product out of EU RoHS legal scope) |
| **China Rohs Regulation** | China RoHS declaration |
| **Environmental Disclosure** | Product Environmental Profile |
| **Weee** | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| **Circularity Profile** | No need of specific recycling operations |
| **California Proposition 65** | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |