# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# PILOT LIGHT 120VAC 30MM TYPE K +OPTIONS

9001KT5

! Discontinued on: Oct 20, 2020

### ① Discontinued

# Main

| Range Of Product          | Harmony 9001K |
|---------------------------|---------------|
| Product Or Component Type | Pilot light   |
| Device Short Name         | 9001K         |

# Complementary

| Bezel Material                                 | Chromium plated metal  |
|--|--|
| Mounting Diameter                              | 30 mm  |
| Shape Of Signaling Unit Head                   | Round  |
| Light Source                                   | incandescent   |
| Bulb Base                                      | BA 9s  |
| Light Block Supply                             | Via integral transformer 380480 V AC 50/60 Hz 6 V)                   |
| Connections - Terminals                        | Screw clamp terminals, 1 x 0.222 x 1.5 mm² conforming to IEC 60947-1 |
| Tightening Torque                              | 0.8 N.m conforming to IEC 60947-1                                    |
| Shape Of Screw Head                            | Cross slotted  |
| Operating Position                             | Any position   |
| [Ui] Rated Insulation Voltage                  | 250 V (pollution degree 2) conforming to IEC 60947-1                 |
| [Uimp] Rated Impulse Withstand Voltage         | 2.5 kV conforming to IEC 60947-1                                     |
| Short-Circuit Protection                       | 10 A cartridge fuse conforming to IEC 60947-5-1                      |
| [Ith] Conventional Free Air<br>Thermal Current | 10 A   |
| Cad Overall Width                              | 54 mm  |
| Cad Overall Height                             | 70 mm  |
| Cad Overall Depth                              | 42 mm  |
| Operating Mode                                 | Push-to-test   |
| Net Weight                                     | 0.21 kg  |

### **Environment**

| Standards | UL 508           |  |
|-----------|------------------|--|
|           | EN/IEC 60947-5-4 |  |
|           | JIS C8201-5-1    |  |
|           | EN/IEC 60947-5-1 |  |
|           | JIS C 852        |  |
|           | CSA C22.2 No 14  |  |
|           | EN/IEC 60947-1   |  |
|           | JIS C8201-1      |  |

| Product Certifications                | UL 508<br>NEMA  |
|---------------------------------------|---|
| Protective Treatment                  | тс  |
| Ambient Air Temperature For Storage   | -4070 °C  |
| Ambient Air Temperature For Operation | -2570 °C  |
| Vibration Resistance                  | 7 gn (f= 2500 Hz) conforming to IEC 60068-2-6             |
| Shock Resistance                      | 50 gn conforming to IEC 60068-2-27                        |
| Overvoltage Category                  | Class II conforming to IEC 61140                          |
| Ip Degree Of Protection               | IP66 conforming to IEC 60529                              |
| Nema Degree Of Protection             | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 4 NEMA 4 |

# Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

# Well-being performance



Mercury Free



Rohs Exemption Information

Yes

## **Certifications & Standards**

| Reach Regulation          | REACh Declaration   |
|---------------------------|---|
| Eu Rohs Directive         | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation     | China RoHS declaration  |
| Environmental Disclosure  | Product Environmental Profile   |
| Weee                      | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   |
| Circularity Profile       | No need of specific recycling operations  Circularity Profile   |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |