Product data sheet

Specifications



(!) Discontinued

ProDis - earth leakage add-on block - Vigi DT40 - 3P + N - 40A - 300mA

A9N21477

() Discontinued on: Oct 14, 2021

Main

| Range | Prodis |
|--|---------------------------------|
| Product Or Component Type | Add-on residual current devices |
| Device Short Name | Vigi DT40 |
| Poles Description | 3P + N |
| Neutral Position | Left |
| [In] Rated Current | 40 A |
| Network Type | AC |
| Earth-Leakage Sensitivity | 300 mA |
| Earth-Leakage Protection Time Delay | Instantaneous |
| Earth-Leakage Protection Class | Type A-SI (Super Immunised) |

Complementary

| Device Location In System | Outgoer |
|---|---|
| Network Frequency | 50 Hz |
| [Ue] Rated Operational Voltage | 400 V AC 50 Hz phase to phase |
| Residual Current Tripping Technology | Voltage independent |
| [Ui] Rated Insulation Voltage | 400 V AC 50 Hz conforming to EN 61009-1 |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV conforming to EN 61009-1 |
| Local Signalling | ON/OFF indication |
| Mounting Mode | Clip-on |
| Mounting Support | DIN rail |
| Electrical Connection To Mcb | By screws |
| 9 Mm Pitches | 4 |
| Height | 81 mm |
| Width | 54 mm |
| Depth | 69 mm |
| Net Weight | 210 g |
| Colour | White |
| Electrical Durability | 10000 cycles |

| Connections - Terminals | Cable downstream 0.7516 mm² rigid Cable downstream 0.3310 mm² flexible |
|-------------------------|---|
| Wire Stripping Length | 13 mm |
| Tightening Torque | 2 N.m |

Environment

| Standards | EN 61009-1 EN 61009-2-1 |
|--|------------------------------|
| Ip Degree Of Protection | IP20 conforming to IEC 60529 |
| Pollution Degree | 3 conforming to EN 61009-1 |
| Tropicalisation | 2 conforming to IEC 60068-1 |
| Relative Humidity | 95 % at 55 °C |
| Operating Altitude | 2000 m |
| Ambient Air Temperature For Operation | -2560 °C |
| Ambient Air Temperature For Storage | -4060 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 8 cm |
| Package 1 Width | 10.5 cm |
| Package 1 Length | 11.5 cm |
| Package 1 Weight | 206 g |

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eq

Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information
Yes

Halogen Free Plastic Parts Product

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |