

2 Switch, AvatarOn, 1-pole 2-way, brass terminal, IP20, light wood

E8332L2_LW_G11

! Discontinued on: Jun 30, 2023

! Discontinued

Main

| Product Or Component Type | Switch |
|---------------------------|-------------------|
| Device Application | Control |
| Load Type | Incandescent lamp |
| | Fluorescent lamp |
| | Resistive |
| | Inductive |
| Colour Tint | Light wood |

Complementary

| • | |
|------------------------------|---|
| Device Presentation | Complete product |
| Rated Current | 16 AX at 250 V AC 50/60 Hz |
| Switch Function | 1-pole 2-way |
| Number Of Gangs | 2 gangs |
| Number Of Rocker | 2 |
| Clamping Connection Capacity | 3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s) |
| Connections - Terminals | Brass terminal |
| Material | Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator |
| Device Mounting | Flush Surface |
| Width | 86 mm |
| Height | 86 mm |
| Depth | 34.2 mm |

Environment

| Ip Degree Of Protection | IP20 |
|--|--------------|
| Maximum Ambient Air Temperature For Operation | 45 °C |
| Operating Altitude | 2000 m |
| Relative Humidity | 095 % |
| Environmental Characteristic | UV resistant |

| Standards | IEC 60669-1 | |
|-----------|----------------|--|
| | SS 227-1 | |
| | BS EN 60669-1 | |
| | MS IEC 60669-1 | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.4 cm |
| Package 1 Width | 8.6 cm |
| Package 1 Length | 8.6 cm |
| Package 1 Weight | 93 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 9.5 cm |
| Package 2 Width | 19 cm |
| Package 2 Length | 19.5 cm |
| Package 2 Weight | 1.024 kg |
| Unit Type Of Package 3 | CAR |
| Number Of Units In Package 3 | 60 |
| Package 3 Height | 21 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 39.5 cm |
| Package 3 Weight | 6.145 kg |

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc
 ✓ Toxic Heavy Metal Free
 ✓ Mercury Free
 ✓ Rohs Exemption Information

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |