

Product data sheet

Specifications



Mureva TUBE - conduit sleeve - grey - Ø50 mm

ENN41350

⚠ Discontinued on: Apr 28, 2022

⚠ Discontinued

Main

Product Range	Mureva TUBE
Product Type	Conduit sleeve
Colour	Grey (RAL 7035)
Quantity Per Package	1 piece

Complementary

Product Destination	Mureva TUBE conduit
Condition Of Use	Indoor/outdoor
Material	PP (polypropylene)
Crush Resistance	750 N/m
Nominal Cross Section	473 mm²
Internal Diameter	46 mm
External Diameter	50 mm
Net Weight	0.048 kg

Environment

Operating Temperature	-5...60 °C
Quality Labels	NF
Standards	EN 50086-2-1 EN 61386-21 : 2004
Ip-Class	IP41
Ik-Class	IK08

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	12 cm
Package 1 Length	5.5 cm
Package 1 Weight	48 g

Contractual warranty

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Warranty

18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations