

# Product data sheet

Specifications



## EVLink PARKING WALL MOUNTED 7KW 1XT2 with shutter RFID EV CHARGING STATION

EVW1S7P04R

⚠ Discontinued on: Jul 1, 2020

⚠ Discontinued

### Main

Range	EVlink
Product Name	EVlink parking
Product Or Component Type	Charging station
Device Short Name	EVW1
Poles Description	1P + N for control circuit 1P + N for power circuit
Mounting Mode	Wall-mounted
Offer Type	Standard
Rated Supply Voltage	230 V AC 50/60 Hz control circuit 230 V AC 50/60 Hz power circuit
Earthing System	TT TN
Socket-Outlet Number	1
Socket-Outlet Type	Right: T2 with shutter / silver plated contacts
Maximum Supply Current	32 A
Max Power	7 kW
Access Control System	Badge RFID

### Complementary

Control Type	1 green illuminated push-button, function: unlock flap 1 red push-button, function: stop
Local Signalling	On charge: 1 LED (green) (flashing) Available: 1 LED (green) Reserved: 1 LED (orange) Not operational: 1 LED (red)
Standards	IEC 61851-22 IEC 61851-1
Product Certifications	CE CB
Height	620 mm
Width	413 mm
Depth	256 mm
Net Weight	33 kg

### Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Ip Degree Of Protection</b>	IP54 off load conforming to IEC 61851-1 IP54 on load conforming to IEC 61851-1
<b>Ik Degree Of Protection</b>	IK10 charging station conforming to IEC 61851-22 IK08 socket-outlet conforming to IEC 61851-22
<b>Ambient Air Temperature For Operation</b>	-30...50 °C conforming to IEC 61851-22
<b>Ambient Air Temperature For Storage</b>	-40...80 °C
<b>Operating Altitude</b>	0...2000 m conforming to IEC 61851-22
<b>Relative Humidity</b>	0...95 %

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	50 cm
<b>Package 1 Width</b>	45 cm
<b>Package 1 Length</b>	68 cm
<b>Package 1 Weight</b>	23.5 kg