Specifications



gearbox with straight teeth GBX- Ø 80 mm- reduction 25:1- < 14arcmin-110 N.m

GBX0800250851G

① Discontinued

Main

| Range Compatibility | Lexium 05 |
|---------------------------|-------------------|
| Product Or Component Type | Planetary gearbox |
| Gear Box Type | Straight teeth |
| Device Short Name | GBX |
| Gearbox External Diameter | 80 mm |
| Product Compatibility | BRH0851 |
| Reduction Ratio | 25:1 |

Complementary

| · · · · · · · · · · · · · · · · · · | | |
|-------------------------------------|--|--|
| Maximum Torsional Backlash | 14 arc.min | |
| Torsional Rigidity | 6.5 N.m/arcmin | |
| Housing Colour | Black | |
| Housing Material | Black anodized aluminium | |
| Shaft Material | C 45 | |
| Additional Information | Lubricated for life | |
| Service Life In Hours | 30000 h at 100 rpm at 30 °C | |
| Efficiency | 94 % | |
| Mounting Position | Any position | |
| Maximum Radial Force Fr | 650 N at 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 $^\circ$ C 950 N at 100 rpm, force applied at mid-distance from output shaft during 10000 hour at 30 $^\circ$ C | |
| Maximum Axial Force Fa | 1200 N at 100 rpm, during 10000 hour at 30°C 900 N at 100 rpm, during 30000 hour at 30°C | |
| Moment Of Inertia | 0.44 g.cm ² | |
| Continuous Output Torque | 110 N.m at 100 rpm at 30 °C | |
| Maximum Output Torque | 176 N.m at 100 rpm at 30 °C | |
| Net Weight | 2.6 kg | |
| | | |

Environment

| Noise Level | 60 dB at 1 m, no-load |
|-------------------------|-----------------------|
| Ip Degree Of Protection | Shaft output: IP54 |

| Ambient Temperature For | -2590 °C |
|-------------------------|----------|
| Operation | |

Contractual warranty

Warranty

18 months