

# Lisse - switched socket - outboard rocker -13 A - 230 V - 2 gangs

GGBL3030S

## Main

Range	Lisse
Aesthetic Name	White moulded
Product Or Component Type	Switched socket
Device Presentation	Complete product
Outlet Standard	British
Colour Tint	Matt white
Quantity Per Set	Set of 1
Type Of Packing	Bag

# Complementary

Switch Function	2-pole
Rated Current	13 A at 250 V AC 50 Hz
Actuator	Rocker
Number Of Gangs	2 gangs
Fixing Mode	By screws
Connections - Terminals	Screw terminals
Material	Urea (carbamide)
Type Of Installation	Indoor
Depth	34 mm
Width	149 mm
Height	87 mm
Net Weight	0.161 kg

## **Environment**

Standards	BS 1363-2
Ip Degree Of Protection	IP20

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.4 cm
Package 1 Width	8.7 cm

Package 1 Length	14.9 cm
Package 1 Weight	175 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	9.5 cm
Package 2 Width	15.5 cm
Package 2 Length	16 cm
Package 2 Weight	943 g
Unit Type Of Package 3	CAR
Number Of Units In Package 3	100
Package 3 Height	33 cm
Package 3 Width	33 cm
Package 3 Length	49 cm
Package 3 Weight	19.45 kg

## Sustainability

Green Premium<sup>TM</sup> label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

## Well-being performance



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Circularity Profile	End of Life Information