

Auxiliary contacts, TeSys GS, 1 NC, early break, front mounting, for GS2 with front/side handle

GS1AM101

Main

| Range Of Product | TeSys | |
|--|---|--|
| Device Short Name | GS1AM | |
| Product Or Component Type | Auxiliary contact | |
| Contact Application | O, I and test position signalling | |
| Range Compatibility | TeSys TeSys GS fuse-switch disconnector FuPact FuPacT GS fuse-switch disconnector | |
| Contacts Type And Composition | 1 NC | |
| Contact Operation | Early-break | |
| [Ith] Conventional Free Air Thermal Current | 10 A (at 40 °C) | |
| [le] Rated Operational Current | 6 A at 120 V AC-15 3 A at 240 V AC-15 1.8 A at 400 V AC-15 1.5 A at 480 V AC-15 2.8 A at 24 V DC-13 1.4 A at 48 V DC-13 0.55 A at 125 V DC-13 0.27 A at 250 V DC-13 0.15 A at 400 V DC-13 | |

Complementary

| Mechanical Durability | 5 Mcycles |
|--------------------------|---------------------|
| Electrical Durability | 1 Mcycles AC-15 |
| Switch Rated Current | 30 A |
| | 32 A |
| | 50 A |
| | 60 A |
| | 63 A |
| | 100 A |
| | 125 A |
| | 160 A |
| | 200 A |
| | 250 A |
| | 315 A |
| | 400 A |
| | 600 A |
| | 630 A |
| | 800 A |
| | 1250 A |
| Fuse Type | NFC |
| | DIN |
| | BS |
| | CC |
| | J |
| Type Of Operating Handle | External frontal |
| | External right side |
| | External left side |

Apr 20, 2024 Life Is On Schneider

| Mounting Location | Front face |
|-------------------|------------|
| Net Weight | 0.015 kg |

Packing Units

| • | |
|------------------------------|--------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.5 cm |
| Package 1 Width | 6 cm |
| Package 1 Length | 8 cm |
| Package 1 Weight | 13 g |
| Unit Type Of Package 2 | S01 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 15 cm |
| Package 2 Width | 15 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 312 g |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ⊘ | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|--|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |