

# Product data sheet

Specifications



## Galaxy VS UPS 15kW 208V with N+1 power module for external batteries, Start-up 5x8

GVSUPS15KRFS

### Overview

Presentation	Highly efficient, easy-to-deploy 15kW, 208V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and one additional power module for N+1 redundancy.
Lead Time	Usually Ships within 2 Weeks

### Main

Main Input Voltage	208 V 3 phases
Other Input Voltage	200 V 220 V
Main Output Voltage	208 V 3 phases
Rated Power In W	15 kW
Rated Power In Va	15 kVA
Battery Type	External battery system Li-Ion (Lithium-Ion) VRLA
Provided Equipment	Dust filter EcoStruxure IT ready (UPS) Installation guide Integrated network management Power modules ship installed Start-up service

### Batteries & Runtime

Battery Voltage	384...480 V DC
Discharge Battery Voltage	307 V DC
Max Current Discharge	51 A

### General

Bypass Voltage Tolerance	+/- 10 %
Redundant	Yes
Product Or Component Type	Uninterruptible power supply (UPS)

### Physical

Colour	White
Height	148.5 cm
Width	52.1 cm
Depth	84.7 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net Weight	250 kg
------------	--------

## Input

Network Frequency	40...70 Hz
Input Voltage Limits	177...239 V 208 V
Maximum Input Current	54 A
Max Short Time Withstand Current	65 kA
Input Harmonic Distortion	Less than 3 % for full load
Load Power Factor	From 0.7 leading to 0.7 lagging without any derating

## Output

Maximum Configurable Power In W	15 kW
Output Frequency	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest Factor	2.5
Wave Type	Sine wave
Output Voltage Tolerance	+/-1% after 50ms
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Bypass Type	Built-in static bypass
Maximum Configurable Power In Va	15 kVA

## Conformance

Standards	IEC 62040-1-1 IEC 62040-2 UL 1778 5th edition FCC part 15 class A IEC 60721-4-2 level 2M2 UL 924
-----------	---

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...3300 ft
Ambient Air Temperature For Storage	-25...55 °C
Storage Relative Humidity	10...80 % non-condensing
Acoustic Level	68 dBA
Heat Dissipation	2802 Btu/h
Ip Degree Of Protection	IP21

## Communications & Management

Control Panel	Touch screen LCD user interface
---------------	---------------------------------

## Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
Package 1 Height	168 cm
Package 1 Width	64 cm
Package 1 Length	99 cm
Package 1 Weight	250 kg

## Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>