Product data sheet

Specifications



integrated servo motor- 12.5 Nm-2000 rpm- keyed shaft-multiturn-with brake-IP65

ILM1402P32F0000

Main

| Range Of Product | PacDrive 3 |
|---------------------------|------------------------------|
| Product Or Component Type | Servo motor integrated drive |
| Device Short Name | ILM |

Complementary

| Complementaly | |
|---------------------------|-----------------------------------------------------------|
| [Us] Rated Supply Voltage | 250700 V |
| Continuous Stall Current | 4.8 A |
| Continuous Stall Torque | 12.5 N.m |
| Peak Stall Torque | 55 N.m |
| Nominal Output Power | 1910 W |
| Nominal Torque | 9.1 N.m |
| Nominal Speed | 2000 rpm |
| Maximum Current Irms | 24 A |
| [In] Rated Current | 3.7 A |
| Shaft End | Keyed |
| Second Shaft | Without second shaft end |
| Shaft Diameter | 24 mm |
| Shaft Length | 50 mm |
| Key Width | 40 mm |
| Feedback Type | Absolute multiturn SinCos Hiperface |
| Speed Feedback Resolution | 128 periods |
| Holding Brake | With |
| Holding Torque | 23 N.m holding brake |
| Mounting Support | International standard flange |
| Motor Flange Size | 140 mm |
| Torque Constant | 2.6 N.m/A at 120 °C |
| Back Emf Constant | 173 V/krpm at 20 °C |
| Number Of Motor Poles | 10 |
| Rotor Inertia | 12.68 kg.cm ² |
| Stator Resistance | 1.9 Ohm at 20 °C for Ph/Ph 1.32 Ohm at 120 °C for Ph/N |

1.32 Ohm at 120 °C for Ph/N

| Stator Inductance | 22 mH at 20 °C for Ph/Ph 11 mH at 120 °C for Ph/N |
|------------------------------------------|------------------------------------------------------|
| Maximum Radial Force Fr | 2430 N at 1000 rpm 1930 N at 2000 rpm |
| Maximum Axial Force Fa | 0.2 x Fr |
| Type Of Cooling | Natural convection |
| Length | 347 mm |
| Number Of Motor Stacks | 2 |
| Centring Collar Diameter | 130 mm |
| Centring Collar Depth | 3.5 mm |
| Number Of Mounting Holes | 4 |
| Mounting Holes Diameter | 11 mm |
| Circle Diameter Of The Mounting Holes | 165 mm |
| Net Weight | 18.5 kg |

Environment

Ip Degree Of Protection

Packing Units

| V | |
|------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 20.0 cm |
| Package 1 Width | 26.0 cm |
| Package 1 Length | 59.0 cm |
| Package 1 Weight | 25.53 kg |

IP65

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eq

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

| Reach Regulation | REACh Declaration |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |