Specifications



Thorsman - TEX-C2 M12x125 - through bolt - set of 25

IMT38012

() Discontinued on: Dec 17, 2020

(!) Discontinued

Main

Range Of Product	Thorsman
Product Or Component Type	Through bolt
Device Short Name	TEX
Provided Equipment	Nut Washer
Quantity Per Set	Set of 25

Complementary

Mounting Support	Concrete Natural rock
Type Of Installation	Indoor
Thread Type	M12
Screw Length	125 mm
Drilling Diameter	12 mm
Minimum Drilling Depth	122 mm
Thickness	Fixture: 030 mm
Embedding Depth	80 mm
Tightening Torque	55 N.m
Material	Steel electro-zinc
Atmospheric-Corrosivity Category	C2
Practical Load Capacity	Pull-out load: 11.4 kN for concrete C20/C25
Serviceability Limit State	Pull-out load: 2070 kg for concrete C20/C25
Ultimate Limit State	Pull-out load: (safety cl 1)1500 kg for concrete C20/C25 Pull-out load: (safety cl 2)1360 kg for concrete C20/C25
Accidental Action	Pull-out load: 3000 kg for concrete C20/C25

Environment

Ambient Air Temperature For	-2060 °C
Operation	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	1.2 cm
Package 1 Width	1.2 cm
Package 1 Length	12.5 cm
Package 1 Weight	108 g

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Eu Rohs Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations