Product data sheet

Specifications

OptiLine 50 - installation trunking - 140 x 63 mm - plastic - white - 2.5 m

INS12450

⚠ **Discontinued on:** Jul 21, 2022

⚠ **Discontinued**

Main

Range Of Product	OptiLine 50
Product Or Component Type	Installation trunking
Colour Tint	White (RAL 9010)
Quantity Per Set	10 m

Complementary

Compartment Partitioning	2 compartments
Trunking Dimension	140 x 63 mm
Trunking Material	Plastic
Front Opening Size	50 mm
Fixing Mode	Screw-fixed By brackets
Material	PVC (polyvinyl chloride)
Length	2500 mm
Height	140 mm
Width	63 mm

Environment

Ambient Air Temperature For Operation	-25…60 °C
Ip Degree Of Protection	IP40
Ik Degree Of Protection	IK07

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	14 cm
Package 1 Width	6.3 cm
Package 1 Length	250 cm
Package 1 Weight	3045 g

Contractual warranty

Warranty	18 months

Life Is On | Schneider Electric

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium 〉

Guide to assess a product's sustainability 〉

Transparency   RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation   REACh Declaration

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

                                             EU RoHS Declaration

---

China Rohs Regulation   China RoHS declaration

                                             Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure   Product Environmental Profile

Circularity Profile   No need of specific recycling operations