

# Product data sheet

Specifications



## OptiLine 50 - pole - free-standing - two installation boxes - anodized

INS40432

⚠ Discontinued on: Jul 19, 2021

⚠ End-of-service on: Feb 2, 2022

⚠ Discontinued

### Main

Range	OptiLine
Product Name	OptiLine 50
Product Type	Pole
Type Of Pole	Two installation boxes
Configuration	Empty
Additional Information	Flexible conduit 2000 mm
Colour	Natural
Quantity Package 1 / Unit	Set of 1

### Complementary

Pole/Post Surface Finish	Anodized
Fixing Mode	Free-standing
Front Opening Size	50 mm
Product Material	Aluminium
Product Material	Aluminium
Height	2150 mm
Width	104 mm

### Environment

Operating Temperature	-15...60 °C
Ip Degree Of Protection	IP30

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	215 cm
Package 1 Width	10.4 cm
Package 1 Length	14 cm
Package 1 Weight	6.41 kg

### Contractual warranty

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Warranty

18 months

# Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



## Transparency

Eu Rohs Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations