Specifications



OptiLine 45 - T-piece - 95-185 x 55 mm - PC/ABS - polar white

ISM10208P

Main

Range Of Product	OptiLine 45
Cabling Installation System	Trunking
Product Type	Т-ріесе
Colour	Polar white (RAL 9003)
Quantity Package 1 / Unit	Set of 1

Complementary

Trunking Material	Plastic	
Trunking Dimension	155 x 55 mm	
	120 x 55 mm	
	185 x 55 mm	
	95 x 55 mm	
Fixing Mode	Snap-fitted	
Product Material	PC/ABS	
Length	117 mm	
Height	52 mm	
Width	57 mm	

Environment

Standards	73/23/EEC 93/68/EEC EN 50085-1:2005 EN 50085-1:2013/A1 EN 50085-2-1:2006 EN 50085-2-1:2011/A1
Operating Temperature	-2560 °C
Ip Degree Of Protection	IP40
Ik Degree Of Protection	IK07

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.4 cm
Package 1 Width	13.7 cm
Package 1 Length	7.8 cm
Package 1 Weight	30.0 g

Unit Type Of Package 2	S03
Number Of Units In Package 2	50
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.985 kg
Package 3 Height	30 cm

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Eq

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations