Product data sheet

Specifications

OptiLine 45 - pole - free-standing - two-sided - natural - 2450 mm

ISM20116

Main

Range	OptiLine
Product Name	OptiLine 45
Cabling Installation System	Pole
Product Type	Pole
Type Of Pole	Two-sided
Pole/Post Surface Finish	Anodized
Pole Fixing Mode	Free-standing

Complementary

Colour	Natural
Front Opening Size	45 mm
Material	Aluminium anodized
Quantity Package 1 / Unit	Set of 1
Height	2450 mm
Depth	90 mm
Width	116 mm

Environment

Standards	73/23/EEC 93/68/EEC EN 50085-1:2005 EN 60598-2-2 IEC 1084-2-4 NF C 68-102 SS 424 10 32
Operating Temperature	-25…60 °C
Ip Degree Of Protection	IP30

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	16.000 cm
Package 1 Width	29.000 cm
Package 1 Length	272.000 cm
Package 1 Weight	9.000 kg

Unit Type Of Package 2	PAL
Number Of Units In Package 2	20
Package 2 Height	94.000 cm
Package 2 Width	120.000 cm
Package 2 Length	370.000 cm
Package 2 Weight	208.000 kg

Contractual warranty

Warranty	18 months

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency   RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation   REACh Declaration

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

                                      EU RoHS Declaration

China Rohs Regulation   China RoHS declaration

                                      Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure   Product Environmental Profile

Circularity Profile   No need of specific recycling operations

---