

OptiLine 45 - pole with 4 boxes - tension-mounted - natural - 3100-3500 mm

ISM20142

#### Main

Range	OptiLine
Product Name	OptiLine 45
Cabling Installation System	Pole
Product Type	Pole
Device Presentation	Empty
Type Of Pole	Four installation boxes
Pole/Post Surface Finish	Anodized
Pole Fixing Mode	Tension-mounted
Socket Additional Information	Unearthed

# Complementary

Additional Information	Adjustability of ceiling fixing 400 mm
Colour	Natural
Front Opening Size	45 mm
Material	Aluminium anodized
Quantity Package 1 / Unit	Set of 1
Height	31003500 mm
Depth	140 mm
Width	149 mm

#### **Environment**

Ip Degree Of Protection IP30

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	16.000 cm
Package 1 Width	29.000 cm
Package 1 Length	332.000 cm
Package 1 Weight	10.000 kg
Unit Type Of Package 2	PAL
Number Of Units In Package 2	20

Package 2 Height	97.000 cm
Package 2 Width	120.000 cm
Package 2 Length	350.000 cm
Package 2 Weight	216.000 kg

## **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations